

```
[ 1240.841901] wlan: [22701:I:ANY] ol_ath_configure_cong_ctrl_max_msdu: 3848: pdev_idx = 0 tx_desc_limit = 24576
[ 1240.841929] wlan: [22701:I:ANY] dp_lag_pdev_set_primary_radio: 55: pdev(a8d6a644) is_primary 1
[ 1240.841963] wlan: [22701:I:ANY] ol_ath_soc_start: 10565: Skip txrx_pdev_attach_target
[ 1240.841971] wlan: [22701:I:ANY] ol_ath_soc_start: 10603: BURSTING enabled by default
[ 1240.845049] wlan: [0:I:ANY] ol_ath_twt_enable_complete_event_handler: 14717: twt enabled.
[ 1240.845049]
[ 1240.849326] wlan: [22701:I:ANY] ol_ath_stats_attach: 2275: periodic_chan_stats: 1
[ 1240.849753] wlan: [22701:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 11
[ 1240.850028] wlan: [22701:I:ANY] ol_ath_configure_cong_ctrl_max_msdu: 3848: pdev_idx = 1 tx_desc_limit = 24576
[ 1240.850056] wlan: [22701:I:ANY] dp_lag_pdev_set_primary_radio: 55: pdev(a8d68d84) is_primary 0
[ 1240.850086] wlan: [22701:I:ANY] ol_ath_soc_start: 10565: Skip txrx_pdev_attach_target
[ 1240.850095] wlan: [22701:I:ANY] ol_ath_soc_start: 10603: BURSTING enabled by default
[ 1240.852917] wlan: [0:I:ANY] ol_ath_twt_enable_complete_event_handler: 14717: twt enabled.
[ 1240.852917]
[ 1240.856550] wlan: [22701:I:ANY] ol_ath_stats_attach: 2275: periodic_chan_stats: 1
[ 1240.857691] wlan: [22701:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 17
[ 1240.857974] wlan: [22701:I:ANY] ol_ath_configure_cong_ctrl_max_msdu: 3848: pdev_idx = 2 tx_desc_limit = 24576
[ 1240.858003] wlan: [22701:I:ANY] dp_lag_pdev_set_primary_radio: 55: pdev(a8d69b04) is_primary 0
[ 1240.858062] wlan: [22701:I:Dynamic Mode Change] ol_ath_check_and_reconfig_hw_mode: 3817: Running with HW mode = 4
[ 1240.859700] wlan: [22701:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 13
[ 1240.859816] wlan: [22701:I:ANY] number of channels: 2G = 13 5G = 0, 6G = 0
[ 1241.216862] wlan: [22853:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 Max_mac_rings 1
[ 1241.216946] wlan: [22853:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 Max_mac_rings 1
[ 1241.217338] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1241.217338]
[ 1241.217396] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:286
[ 1241.217396]
[ 1241.217427] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1241.217427]
[ 1241.217454] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1241.217454]
[ 1241.234105] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1241.234105]
[ 1241.234166] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1241.234166]
[ 1241.234197] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1241.234197]
[ 1241.234224] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1241.234224]
[ 1241.262971] wlan: [22874:I:ANY] wlan_cfg80211_set_hwaddr: 6591: wlan_cfg80211_set_hwaddr :10:0c:6b:44:ff:af ret: 0
[ 1241.327303] wlan: [22883:I:ANY] ol_ath_set_config_param: 1664: set TXBF_SND_PERIOD: value 100 wmi_status 0
[ 1241.523046] wlan: [0:I:ANY] dp_lag_soc_enable: 102: pdev(a8d68d84) Enabling DBDC Repeater 0
[ 1241.523158] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message passed
[ 1241.523170] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message passed
[ 1241.523179] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message passed
[ 1241.523189] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message passed
[ 1241.667514] wlan: [0:I:ANY] ol_ath_set_config_param: 2416: Disconnect_timeout value: 10
[ 1241.732626] wlan: [0:I:ANY] ol_ath_set_config_param: 2422: Reconfiguration_timeout value:60
[ 1242.220052] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
```

```
[ 1242.220052]
[ 1242.220125] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:286
[ 1242.220125]
[ 1242.220148] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1242.220148]
[ 1242.220169] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1242.220169]
[ 1242.236770] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1242.236770]
[ 1242.236836] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1242.236836]
[ 1242.236873] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1242.236873]
[ 1242.236902] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1242.236902]
[ 1242.333613] wlan: [23329:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath1 : clone params: 0x00000001
[ 1242.333695] wlan: [23329:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 10:0c:6b
:44:ff:af
[ 1242.333784] wlan: [23329:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x1
[ 1242.333784]
[ 1242.334117] wlan: [23329:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1242.334158] wlan: [23329:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1242.334165] wlan: [23329:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1242.334184] wlan: [23329:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Trigged
[ 1242.334265] wlan: [23329:I:ANY] MBO Initialized
[ 1242.334274] wlan: [23329:I:ANY] OCE Initialized
[ 1242.334305] wlan: [23329:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 38 nss_id -1
[ 1242.334314] wlan: [23329:I:ANY] NSS radio_if 29
[ 1242.334367] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1242.334390] wlan: [23329:I:ANY] osif_nss_ol_vap_create: 1393: vap create ad495640
: if_num 38
[ 1242.334787] wlan: [23329:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1242.334795] wlan: [23329:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1242.338220] wlan: [23329:I:ANY] VAP device ath1 created osifp: (ad495640) os_if:
(b91c0000)
[ 1243.221784] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1243.221784]
[ 1243.221855] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:286
[ 1243.221855]
[ 1243.221912] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1243.221912]
[ 1243.221951] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1243.221951]
[ 1243.237588] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1243.237588]
[ 1243.237649] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1243.237649]
[ 1243.237684] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1243.237684]
[ 1243.237704] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1243.237704]
[ 1243.457841] device ath1 entered promiscuous mode
[ 1243.458003] br-lan: port 5(ath1) entered listening state
[ 1243.458060] br-lan: port 5(ath1) entered listening state
[ 1243.459173] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3709: vap-0(ath1):ACS Params
[ 1243.459189] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3712: ht_enabled:1|ht40_enab
led:0|vht_enabled:1|hw_mode:29|chwidth:20|
[ 1243.459201] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS
started: vap:0xb91c0000
[ 1243.746656] wlan: [23861:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1243.779596] wlan: [23880:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath11 : clone params: 0x00000001
[ 1243.779672] wlan: [23880:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 16:0c:6b
:44:ff:af
```

```
[ 1243.779749] wlan: [23880:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmode=IEEE80211_M_HOSTAP, flags=0x1
[ 1243.779749]
[ 1243.780042] wlan: [23880:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1243.780093] wlan: [23880:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_bfer:0
[ 1243.780100] wlan: [23880:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1243.780119] wlan: [23880:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT sounding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1243.780199] wlan: [23880:I:ANY] MBO Initialized
[ 1243.780207] wlan: [23880:I:ANY] OCE Initialized
[ 1243.780240] wlan: [23880:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VAP create IF 39 nss_id -1
[ 1243.780248] wlan: [23880:I:ANY] NSS radio_if 29
[ 1243.780294] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration success: 0
[ 1243.780314] wlan: [23880:I:ANY] osif_nss_ol_vap_create: 1393: vap create b80e5640 : if_num 39
[ 1243.780671] wlan: [23880:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:1|TSO:1|LRO:0
[ 1243.780678] wlan: [23880:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1243.784607] wlan: [23880:I:ANY] VAP device ath11 created osifp: (b80e5640) os_if: (a7d30000)
[ 1243.799447] device ath11.4093 entered promiscuous mode
[ 1243.799462] device ath11 entered promiscuous mode
[ 1243.800228] br-guest: port 5(ath11.4093) entered forwarding state
[ 1243.800302] br-guest: port 5(ath11.4093) entered forwarding state
[ 1243.819401] device ath11.4094 entered promiscuous mode
[ 1243.820203] br-lan: port 6(ath11.4094) entered listening state
[ 1243.820282] br-lan: port 6(ath11.4094) entered listening state
[ 1244.222898] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1244.222898]
[ 1244.222959] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:286
[ 1244.222959]
[ 1244.222988] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1244.222988]
[ 1244.223018] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1244.223018]
[ 1244.238515] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1244.238515]
[ 1244.238570] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1244.238570]
[ 1244.238591] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1244.238591]
[ 1244.238609] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1244.238609]
[ 1245.115420] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3709: vap-1(ath11):ACS Params
[ 1245.115436] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3712: ht_enabled:1|ht40_enabled:0|vht_enabled:1|hw_mode:29|chwidth:20|
[ 1245.115449] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS started: vap:0xa7d30000
[ 1245.195959] wlan: [24434:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fragmentation with HT mode NOT ALLOWED!!
[ 1245.195974] wlan: [24434:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fragmentation with HT mode NOT ALLOWED!!
[ 1245.227897] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1245.227897]
[ 1245.227931] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1245.227931]
[ 1245.227953] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1245.227953]
[ 1245.236102] wlan: [24455:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary mode 6 for interface: ath12 : clone params: 0x00000001
[ 1245.236167] wlan: [24455:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 1a:0c:6b:44:ff:af
[ 1245.236271] wlan: [24455:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmode=IEEE80211_M_HOSTAP, flags=0x1
[ 1245.236271]
[ 1245.236533] wlan: [24455:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1245.236579] wlan: [24455:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
```

```
fer:0
[ 1245.236586] wlan: [24455:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1245.236604] wlan: [24455:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Trigged
[ 1245.236668] wlan: [24455:I:ANY] MBO Initialized
[ 1245.236675] wlan: [24455:I:ANY] OCE Initialized
[ 1245.236709] wlan: [24455:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 40 nss_id -1
[ 1245.236717] wlan: [24455:I:ANY] NSS radio_if 29
[ 1245.236779] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1245.236797] wlan: [24455:I:ANY] osif_nss_ol_vap_create: 1393: vap create b5e535c0
: if_num 40
[ 1245.237160] wlan: [24455:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1245.237167] wlan: [24455:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1245.239694] wlan: [24455:I:ANY] VAP device ath12 created osifp: (b5e535c0) os_if:
(a9bb8000)
[ 1245.239925] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1245.239925]
[ 1245.239978] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1245.239978]
[ 1245.240000] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1245.240000]
[ 1245.240025] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1245.240025]
[ 1245.451699] br-lan: port 5(ath1) entered learning state
[ 1245.791685] br-guest: port 5(ath11.4093) entered forwarding state
[ 1245.811702] br-lan: port 6(ath11.4094) entered learning state
[ 1246.228444] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1246.228444]
[ 1246.228479] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1246.228479]
[ 1246.228515] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1246.228515]
[ 1246.240742] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1246.240742]
[ 1246.240793] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1246.240793]
[ 1246.240814] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1246.240814]
[ 1246.240832] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1246.240832]
[ 1246.452654] device ath12 entered promiscuous mode
[ 1246.452849] br-guest: port 6(ath12) entered forwarding state
[ 1246.452900] br-guest: port 6(ath12) entered forwarding state
[ 1246.454022] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3709: vap-2(ath12):ACS Param
s
[ 1246.454038] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3712: ht_enabled:1|ht40_enab
led:0|vht_enabled:1|hw_mode:29|chwidth:20|
[ 1246.454052] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS
started: vap:0xa9bb8000
[ 1246.704946] wlan: [25073:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1246.704960] wlan: [25073:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1246.704968] wlan: [25073:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1246.733597] wlan: [25080:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath13 : clone params: 0x00005001
[ 1246.733676] wlan: [25080:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 1e:0c:6b
:44:ff:af
[ 1246.733781] wlan: [25080:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x5001
[ 1246.733781]
[ 1246.734046] wlan: [25080:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1246.734094] wlan: [25080:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1246.734101] wlan: [25080:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1246.734120] wlan: [25080:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Trigged
[ 1246.734201] wlan: [25080:I:ANY] MBO Initialized
```

```
[ 1246.734209] wlan: [25080:I:ANY] OCE Initialized
[ 1246.734245] wlan: [25080:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 41 nss_id -1
[ 1246.734254] wlan: [25080:I:ANY] NSS radio_if 29
[ 1246.734302] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1246.734319] wlan: [25080:I:ANY] osif_nss_ol_vap_create: 1393: vap create a6d65640
: if_num 41
[ 1246.734663] wlan: [25080:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1246.734670] wlan: [25080:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1246.737770] wlan: [25080:I:ANY] VAP device ath13 created osifp: (a6d65640) os_if:
(adaa0000)
[ 1246.983649] wlan: [25173:I:ANY] DES SSID SET=SM_0
[ 1247.238504] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1247.238504] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1247.238554] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1247.238576] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1247.238576] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1247.245352] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1247.245352] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1247.245410] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1247.245410] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1247.245433] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1247.245433] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1247.245454] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1247.451701] br-lan: topology change detected, propagating
[ 1247.451719] br-lan: port 5(ath1) entered forwarding state
[ 1247.811699] br-lan: topology change detected, propagating
[ 1247.811715] br-lan: port 6(ath11.4094) entered forwarding state
[ 1248.031687] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS
started: vap:0xadaa0000
[ 1248.238698] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1248.238698] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1248.238744] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1248.238744] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1248.238776] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1248.238776] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1248.245645] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1248.245645] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1248.245694] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1248.245694] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1248.245727] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1248.245727] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1248.245745] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1248.245745] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1248.257814] wlan: [25646:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS
started: vap:0xadaa0000
[ 1248.451690] br-guest: port 6(ath12) entered forwarding state
[ 1249.239608] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1249.239608] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1249.239649] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1249.239649] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1249.239670] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1249.239670] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1249.245904] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1249.245904] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1249.245962] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1249.245962] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1249.245986] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1249.245986] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1249.246008] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1249.246008] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1249.512737] wlan: [26368:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 8
[ 1249.513309] wlan: [26368:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=58
[ 1249.513935] wlan: [26368:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 8
[ 1249.514083] wlan: [26368:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=58
[ 1249.514111] wlan: [26368:I:ANY] number of channels: 2G = 0 5G = 8, 6G = 0
[ 1249.514154] wlan: [2838:I:ANY] ol_acfg_handle_wifi_ioctl: 446: ol_acfg_handle_wif
```

```
i_ioctl: req->cmd=76 not valid for radio interface, it's for VAP
[ 1249.754573] wlan: [26445:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
  2 Max_mac_rings 1
[ 1249.754695] wlan: [26445:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
  1 Max_mac_rings 1
[ 1249.789401] wlan: [26455:I:ANY] wlan_cfg80211_set_hwaddr: 6591: wlan_cfg80211_set
_hwaddr :10:0c:6b:44:ff:b0 ret: 0
[ 1249.827968] wlan: [26463:I:ANY] ol_ath_set_config_param: 1664: set TXBF_SND_PERIO
D: value 100 wmi_status 0
[ 1249.973216] wlan: [0:I:ANY] dp_lag_soc_enable: 102: pdev(a8d6a644) Enabling DBDC
Repeater 0
[ 1249.973329] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1249.973338] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1249.973345] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1249.973352] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1250.078768] wlan: [1827:I:ANY] vap-0(ath1): ACS result PCH 5 freq 2432, SCH 1 fre
q 2412, hw_mode 1 chwidth 40, vht_seg0 3 freq 2422, vht_seg1 0 freq 0
[ 1250.078886] wlan: [1827:I:ANY] vap-1(ath11): ACS result PCH 5 freq 2432, SCH 1 fr
eq 2412, hw_mode 1 chwidth 40, vht_seg0 3 freq 2422, vht_seg1 0 freq 0
[ 1250.078965] wlan: [1827:I:ANY] vap-2(ath12): ACS result PCH 5 freq 2432, SCH 1 fr
eq 2412, hw_mode 1 chwidth 40, vht_seg0 3 freq 2422, vht_seg1 0 freq 0
[ 1250.079262] wlan: [1827:I:ANY] vdev[3]: Mgt Rate:1000(kbps)
[ 1250.079291] wlan: [1827:I:ANY] ieee80211_acs_scan_evhandler: 4759: lock held dura
tion: 1(ms)
[ 1250.079611] wlan: [0:I:ANY] ol_ath_set_config_param: 2416: Disconnect_timeout val
ue: 10
[ 1250.101866] wlan: [2893:I:ANY] DES SSID SET=reality_optout
[ 1250.101888] wlan: [2893:I:ANY] wlan_cfg80211_chan_to_phymode: 1239: wlan_cfg80211
_chan_to_phymode: band:0 width: 2 channel_cfreq: 2432 center_freq1: 2422 chandef.cen
ter_freq2: 0 flags: 0
[ 1250.102007] wlan: [2893:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1250.102007] Channel is configured already!!
[ 1250.129789] wlan: [0:I:ANY] ol_ath_set_config_param: 2422: Reconfiguration_timeou
t value:60
[ 1250.143947] wlan: [2893:I:ANY] DES SSID SET=NETGEAR_ORBI_hidden43
[ 1250.143966] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
27
[ 1250.144162] wlan: [2893:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1250.144162] Channel is configured already!!
[ 1250.170617] wlan: [2893:I:ANY] DES SSID SET=pocket-reality_optout
[ 1250.170637] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
27
[ 1250.170778] wlan: [2893:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1250.170778] Channel is configured already!!
[ 1250.193235] wlan: [0:I:CMN_MLME] vdev[3] ieee chan:5 freq:2432
[ 1250.193430] wlan: [0:I:ANY] vdev[3]: Mgt Rate:1000(kbps)
[ 1250.193489] wlan: [0:I:ANY] vdev[3]: Mgt Rate:1000(kbps)
[ 1250.223350] wlan: [0:I:CMN_MLME] vdev[0] ieee chan:5 freq:2432
[ 1250.223682] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1250.223682] FD Interval should be a factor of BI.
[ 1250.223682] Disabling FD
[ 1250.223682]
[ 1250.223956] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1250.223956] FD Interval should be a factor of BI.
[ 1250.223956] Disabling FD
[ 1250.223956]
[ 1250.224016] wlan: [0:I:ANY] vdev[0]: Mgt Rate:1000(kbps)
[ 1250.224059] wlan: [0:I:ANY] vdev[0]: Mgt Rate:1000(kbps)
[ 1250.224163] wlan: [0:I:CMN_MLME] vdev[1] ieee chan:5 freq:2432
[ 1250.224447] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1250.224447] FD Interval should be a factor of BI.
[ 1250.224447] Disabling FD
[ 1250.224447]
[ 1250.224629] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1250.224629] FD Interval should be a factor of BI.
```

```
[ 1250.224629] Disabling FD
[ 1250.224629]
[ 1250.224679] wlan: [0:I:ANY] vdev[1]: Mgt Rate:1000(kbps)
[ 1250.224717] wlan: [0:I:ANY] vdev[1]: Mgt Rate:1000(kbps)
[ 1250.224800] wlan: [0:I:CMN_MLME] vdev[2] ieee chan:5 freq:2432
[ 1250.225079] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1250.225079] FD Interval should be a factor of BI.
[ 1250.225079] Disabling FD
[ 1250.225079]
[ 1250.225318] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1250.225318] FD Interval should be a factor of BI.
[ 1250.225318] Disabling FD
[ 1250.225318]
[ 1250.225369] wlan: [0:I:ANY] vdev[2]: Mgt Rate:1000(kbps)
[ 1250.225412] wlan: [0:I:ANY] vdev[2]: Mgt Rate:1000(kbps)
[ 1250.241348] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1250.241348]
[ 1250.241381] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1250.241381]
[ 1250.241403] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1250.241403]
[ 1250.246707] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1250.246707]
[ 1250.246740] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1250.246740]
[ 1250.246762] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1250.246762]
[ 1250.702834] wlan: [26888:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath0 : clone params: 0x00000001
[ 1250.702896] wlan: [26888:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 10:0c:6b
:44:ff:b0
[ 1250.702980] wlan: [26888:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ea0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x1
[ 1250.702980]
[ 1250.703326] wlan: [26888:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1250.703373] wlan: [26888:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1250.703380] wlan: [26888:I:ANY] ol_ath_vap_set_param: 2243: he bf_cap=0x7b
[ 1250.703399] wlan: [26888:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1250.703483] wlan: [26888:I:ANY] MBO Initialized
[ 1250.703491] wlan: [26888:I:ANY] OCE Initialized
[ 1250.703521] wlan: [26888:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 42 nss_id -1
[ 1250.703530] wlan: [26888:I:ANY] NSS radio_if 28
[ 1250.703692] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1250.703715] wlan: [26888:I:ANY] osif_nss_ol_vap_create: 1393: vap create affd0500
: if_num 42
[ 1250.704150] wlan: [26888:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1250.704161] wlan: [26888:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1250.707302] wlan: [26888:I:ANY] VAP device ath0 created osifp: (affd0500) os_if:
(af2f0000)
[ 1251.242564] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1251.242564]
[ 1251.242595] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1251.242595]
[ 1251.242616] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1251.242616]
[ 1251.247700] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1251.247700]
[ 1251.247745] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1251.247745]
[ 1251.247766] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1251.247766]
[ 1251.813971] device ath0 entered promiscuous mode
[ 1251.814559] br-lan: port 7(ath0) entered listening state
[ 1251.814621] br-lan: port 7(ath0) entered listening state
[ 1251.836217] wlan: [2893:I:ANY] DES SSID SET=reality_optout
```

```
[ 1251.836235] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
30
[ 1251.836726] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1252.010848] wlan: [0:I:CMN_MLME] vdev[4] ieee chan:40 freq:5200
[ 1252.011180] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1252.011180] FD Interval should be a factor of BI.
[ 1252.011180] Disabling FD
[ 1252.011180]
[ 1252.011385] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1252.011385] FD Interval should be a factor of BI.
[ 1252.011385] Disabling FD
[ 1252.011385]
[ 1252.011435] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1252.011474] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1252.105425] wlan: [27391:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1252.114572] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1252.132010] wlan: [0:I:CMN_MLME] vdev[4] ieee chan:40 freq:5200
[ 1252.132332] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1252.132332] FD Interval should be a factor of BI.
[ 1252.132332] Disabling FD
[ 1252.132332]
[ 1252.132593] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1252.132593] FD Interval should be a factor of BI.
[ 1252.132593] Disabling FD
[ 1252.132593]
[ 1252.132650] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1252.132695] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1252.137700] wlan: [27405:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath01 : clone params: 0x00000001
[ 1252.137792] wlan: [27405:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 16:0c:6b
:44:ff:b0
[ 1252.137886] wlan: [27405:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ea0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x1
[ 1252.137886]
[ 1252.138155] wlan: [27405:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1252.138201] wlan: [27405:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1252.138208] wlan: [27405:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1252.138227] wlan: [27405:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1252.138295] wlan: [27405:I:ANY] MBO Initialized
[ 1252.138302] wlan: [27405:I:ANY] OCE Initialized
[ 1252.138335] wlan: [27405:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 43 nss_id -1
[ 1252.138344] wlan: [27405:I:ANY] NSS radio_if 28
[ 1252.138385] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1252.138404] wlan: [27405:I:ANY] osif_nss_ol_vap_create: 1393: vap create b32b4600
: if_num 43
[ 1252.138758] wlan: [27405:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1252.138766] wlan: [27405:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1252.142092] wlan: [27405:I:ANY] VAP device ath01 created osifp: (b32b4600) os_if:
(afab0000)
[ 1252.243742] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1252.243742]
[ 1252.243776] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1252.243776]
[ 1252.248575] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1252.248575]
[ 1252.248606] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1252.248606]
[ 1252.248627] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1252.248627]
[ 1252.644948] wlan: [15868:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
```



```
2 Max_mac_rings 1
[ 1252.645010] wlan: [15868:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
1 Max_mac_rings 1
[ 1253.244554] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1253.244554]
[ 1253.244584] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1253.244584]
[ 1253.249822] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1253.249822]
[ 1253.249866] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1253.249866]
[ 1253.249906] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1253.249906]
[ 1253.306016] device ath01 entered promiscuous mode
[ 1253.306434] br-guest: port 7(ath01) entered forwarding state
[ 1253.306498] br-guest: port 7(ath01) entered forwarding state
[ 1253.326314] wlan: [2893:I:ANY] DES SSID SET=pocket-reality_optout
[ 1253.326344] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
30
[ 1253.326682] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1253.327302] wlan: [0:I:CMN_MLME] vdev[5] ieee chan:40 freq:5200
[ 1253.327611] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1253.327611] FD Interval should be a factor of BI.
[ 1253.327611] Disabling FD
[ 1253.327611]
[ 1253.327798] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1253.327798] FD Interval should be a factor of BI.
[ 1253.327798] Disabling FD
[ 1253.327798]
[ 1253.327846] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1253.327885] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1253.582143] wlan: [27897:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1253.582158] wlan: [27897:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1253.591944] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1253.592532] wlan: [0:I:CMN_MLME] vdev[5] ieee chan:40 freq:5200
[ 1253.592837] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1253.592837] FD Interval should be a factor of BI.
[ 1253.592837] Disabling FD
[ 1253.592837]
[ 1253.593025] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1253.593025] FD Interval should be a factor of BI.
[ 1253.593025] Disabling FD
[ 1253.593025]
[ 1253.593080] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1253.593121] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1253.615302] wlan: [27908:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath02 : clone params: 0x00005001
[ 1253.615371] wlan: [27908:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 1a:0c:6b
:44:ff:b0
[ 1253.615453] wlan: [27908:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ea0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x5001
[ 1253.615453]
[ 1253.615789] wlan: [27908:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1253.615828] wlan: [27908:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1253.615835] wlan: [27908:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1253.615867] wlan: [27908:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1253.615977] wlan: [27908:I:ANY] MBO Initialized
[ 1253.615985] wlan: [27908:I:ANY] OCE Initialized
[ 1253.616020] wlan: [27908:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 44 nss_id -1
[ 1253.616028] wlan: [27908:I:ANY] NSS radio_if 28
[ 1253.616127] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
```

```
success: 0
[ 1253.616178] wlan: [27908:I:ANY] osif_nss_ol_vap_create: 1393: vap create a8da5640
: if_num 44
[ 1253.616584] wlan: [27908:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1253.616591] wlan: [27908:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1253.620201] wlan: [27908:I:ANY] VAP device ath02 created osifp: (a8da5640) os_if:
(aeb98000)
[ 1253.811712] br-lan: port 7(ath0) entered learning state
[ 1253.865079] wlan: [27988:I:ANY] DES SSID SET=SM_1
[ 1253.934106] wlan: [28003:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1253.934106] Channel is configured already!!
[ 1254.245730] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1254.245730]
[ 1254.245762] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1254.245762]
[ 1254.250961] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1254.250961]
[ 1254.250991] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1254.250991]
[ 1255.016302] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1255.017013] wlan: [0:I:CMN_MLME] vdev[6] ieee chan:40 freq:5200
[ 1255.017208] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1255.017270] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1255.018456] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 M
ax_mac_rings 1
[ 1255.018504] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 M
ax_mac_rings 1
[ 1255.018530] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 M
ax_mac_rings 1
[ 1255.018548] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 M
ax_mac_rings 1
[ 1255.246883] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1255.246883]
[ 1255.246916] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1255.246916]
[ 1255.251542] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1255.252266] wlan: [0:I:CMN_MLME] vdev[6] ieee chan:40 freq:5200
[ 1255.252466] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1255.252509] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1255.252830] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1255.252830]
[ 1255.252853] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1255.252853]
[ 1255.301701] br-guest: port 7(ath01) entered forwarding state
[ 1255.811720] br-lan: topology change detected, propagating
[ 1255.811745] br-lan: port 7(ath0) entered forwarding state
[ 1256.247523] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1256.247523]
[ 1256.247551] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1256.247551]
[ 1256.252365] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1256.252365]
[ 1256.252398] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1256.252398]
[ 1256.252398]
[ 1256.614136] wlan: [29208:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 11
[ 1256.614971] wlan: [29208:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=106
[ 1256.614983] wlan: [29208:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=122
[ 1256.615648] wlan: [29208:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 11
[ 1256.615784] wlan: [29208:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=106
[ 1256.615791] wlan: [29208:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=122
[ 1256.615819] wlan: [29208:I:ANY] number of channels: 2G = 0 5G = 11, 6G = 0
[ 1256.615909] wlan: [2838:I:ANY] ol_acfg_handle_wifi_ioctl: 446: ol_acfg_handle_wif
i_ioctl: req->cmd=76 not valid for radio interface, it's for VAP
[ 1256.927781] wlan: [29322:I:ANY] wlan_cfg80211_set_hwaddr: 6591: wlan_cfg80211_set
_hwaddr :10:0c:6b:44:ff:b1 ret: 0
[ 1256.970748] wlan: [29345:I:ANY] ol_ath_set_config_param: 1664: set TXBF_SND_PERIO
```

```
D: value 100 wmi_status 0
[ 1257.024802] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1257.024836] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1257.024959] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1257.027592] wlan: [0:E:ANY] wlan_node_get_disassoc_stats: 846: peer_stats is null
[ 1257.036055] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1257.036108] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1257.036291] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1257.118566] wlan: [0:I:ANY] dp_lag_soc_enable: 102: pdev(a8d69b04) Enabling DBDC
Repeater 0
[ 1257.118672] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1257.118680] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1257.118687] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1257.118694] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1257.225077] wlan: [0:I:ANY] ol_ath_set_config_param: 2416: Disconnect_timeout val
ue: 10
[ 1257.247931] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1257.247931]
[ 1257.247982] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1257.247982]
[ 1257.252969] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1257.252969]
[ 1257.252996] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1257.252996]
[ 1257.272517] wlan: [0:I:ANY] ol_ath_set_config_param: 2422: Reconfiguration_timeou
t value:60
[ 1257.628357] wlan: [29607:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath2 : clone params: 0x00000001
[ 1257.628429] wlan: [29607:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 10:0c:6b
:44:ff:b1
[ 1257.628514] wlan: [29607:I:ANY] wlan_vap_create: 1599: devhandle=0xb4f40500, opmo
de=IEEE80211_M_HOSTAP, flags=0x1
[ 1257.628514]
[ 1257.628884] wlan: [29607:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1257.628931] wlan: [29607:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1257.628938] wlan: [29607:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1257.628955] wlan: [29607:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1257.629034] wlan: [29607:I:ANY] MBO Initialized
[ 1257.629043] wlan: [29607:I:ANY] OCE Initialized
[ 1257.629073] wlan: [29607:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 45 nss_id -1
[ 1257.629081] wlan: [29607:I:ANY] NSS radio_if 30
[ 1257.629122] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1257.629141] wlan: [29607:I:ANY] osif_nss_ol_vap_create: 1393: vap create b974b5c0
: if_num 45
[ 1257.629502] wlan: [29607:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1257.629508] wlan: [29607:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1257.635406] wlan: [29607:I:ANY] VAP device ath2 created osifp: (b974b5c0) os_if:
(af200000)
[ 1257.653509] device ath2.4093 entered promiscuous mode
[ 1257.653524] device ath2 entered promiscuous mode
[ 1257.653879] br-guest: port 8(ath2.4093) entered forwarding state
[ 1257.653937] br-guest: port 8(ath2.4093) entered forwarding state
[ 1257.667390] device ath2.4094 entered promiscuous mode
[ 1257.667725] br-lan: port 8(ath2.4094) entered listening state
[ 1257.667792] br-lan: port 8(ath2.4094) entered listening state
[ 1258.248657] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1258.248657]
[ 1258.248692] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1258.248692]
[ 1258.253899] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1258.253899]
[ 1258.254006] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1258.254006]
```

```
[ 1259.023133] wlan: [2893:I:ANY] DES SSID SET=NETGEAR_ORBI_hidden43
[ 1259.023153] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
30
[ 1259.023562] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1259.038967] wlan: [0:I:CMN_MLME] vdev[7] ieee chan:108 freq:5540
[ 1259.039328] wlan: [0:I:ANY] vdev[7]: Mgt Rate:6000(kbps)
[ 1259.039713] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5500.
[ 1259.039713]
[ 1259.039738] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5520.
[ 1259.039738]
[ 1259.039759] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5540.
[ 1259.039759]
[ 1259.039780] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5560.
[ 1259.039780]
[ 1259.101372] wlan: [30030:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1259.111178] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1259.125776] wlan: [0:I:CMN_MLME] vdev[7] ieee chan:108 freq:5540
[ 1259.125993] wlan: [0:I:ANY] vdev[7]: Mgt Rate:6000(kbps)
[ 1259.126397] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5500.
[ 1259.126397]
[ 1259.126422] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5520.
[ 1259.126422]
[ 1259.126463] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5540.
[ 1259.126463]
[ 1259.126523] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5560.
[ 1259.126523]
[ 1259.249515] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1259.249515]
[ 1259.249549] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1259.249549]
[ 1259.254567] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1259.254567]
[ 1259.254596] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1259.254596]
[ 1259.651686] br-guest: port 8(ath2.4093) entered forwarding state
[ 1259.661716] br-lan: port 8(ath2.4094) entered learning state
[ 1260.280159] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1260.280159]
[ 1260.280317] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1260.280317]
[ 1260.673569] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1260.673569]
[ 1260.673602] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1260.673602]
[ 1261.254661] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1261.254661]
[ 1261.254690] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1261.254690]
[ 1261.281965] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1261.281965]
[ 1261.281993] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1261.281993]
[ 1261.661708] br-lan: topology change detected, propagating
[ 1261.661722] br-lan: port 8(ath2.4094) entered forwarding state
[ 1262.255731] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1262.255731]
[ 1262.255767] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1262.255767]
[ 1262.282874] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1262.282874]
[ 1262.282902] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1262.282902]
```

```
[ 1263.256524] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1263.256524]
[ 1263.256566] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1263.256566]
[ 1263.283560] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1263.283560]
[ 1263.283588] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1263.283588]
[ 1264.256953] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1264.256953]
[ 1264.256985] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1264.256985]
[ 1264.284467] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1264.284467]
[ 1264.284509] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1264.284509]
[ 1265.259329] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1265.259329]
[ 1265.259360] wlan: [15868:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1265.259360]
[ 1265.286183] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:281
[ 1265.286183]
[ 1265.286211] wlan: [15869:I:ANY] ald_nl_receive: Invalid interface index:289
[ 1265.286211]
[ 1265.851320] wlan: [32436:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1265.851344] wlan: [32436:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
[ 1265.851396] wlan: [32436:I:ANY] wlan_set_param: 952: Configure hifi 952 entry_cn
t 2
[ 1265.922699] wlan: [32480:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1265.922713] wlan: [32480:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
[ 1265.922749] wlan: [32480:I:ANY] wlan_set_param: 952: Configure hifi 952 entry_cn
t 2
[ 1265.997475] wlan: [32523:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1265.997491] wlan: [32523:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
[ 1266.067095] wlan: [32560:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1266.067117] wlan: [32560:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
[ 1278.928838] wlan: [2893:I:ANY] Skip bcast de-auth reason code 3, handled in VDEV
down
[ 1278.982350] device ath1 left promiscuous mode
[ 1278.982508] br-lan: port 5(ath1) entered disabled state
[ 1278.990608] wlan: [0:I:CMN_MLME] PSOC_0 VDEV_0 Sending bcast deauth and DELETE_AL
L_PEER, clients: 8
[ 1279.025560] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1279.025593] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1279.113819] wlan: [4959:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach ad495640:
if_num 38
[ 1279.113836] wlan: [4959:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interf
ace Node :38 of type:6
[ 1279.119095] wlan: [0:I:ANY] osif_nss_vdev_set_cfg: 2021: vap transmit called on
invalid interface
[ 1279.119519] wlan: [4959:I:ANY] ieee80211_mbo_vdetach: MBO terminated
[ 1279.119519]
[ 1279.119534] wlan: [4959:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1279.119534]
[ 1279.119686] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_del
_resp: mac: 10:0c:6b:44:ff:af vdevid: 0 Unable to find vdev
[ 1279.120411] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdevid: 984: Get MPSTA
: vdev is NULL
[ 1280.117995] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1280.118161] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.118181] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.118400] wlan: [2765:I:ANY] ath_band_steering_netlink_receive: 118: ath_band_s
teering_netlink_receive: Invalid interface index:292
[ 1280.118478] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:292
[ 1280.118478]
[ 1280.120160] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1280.120302] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.120322] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.120882] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
```

```
[ 1280.121011] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.121030] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.122048] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1280.122234] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.122260] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.123957] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1280.125158] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.125189] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.128896] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1280.129137] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.129165] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.145706] wlan: [2893:I:ANY] Skip bcst de-auth reason code 3, handled in VDEV
down
[ 1280.154138] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1280.154297] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.154316] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1280.287275] device ath11 left promiscuous mode
[ 1280.289416] br-lan: port 6(ath11.4094) entered disabled state
[ 1280.304977] br-guest: port 5(ath11.4093) entered disabled state
[ 1280.343471] device ath11.4093 left promiscuous mode
[ 1280.343509] br-guest: port 5(ath11.4093) entered disabled state
[ 1280.346254] device ath11.4094 left promiscuous mode
[ 1280.346283] br-lan: port 6(ath11.4094) entered disabled state
[ 1280.382891] wlan: [5109:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach b80e5640:
if_num 39
[ 1280.382906] wlan: [5109:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interf
ace Node :39 of type:6
[ 1280.388117] wlan: [0:I:ANY] osif_nss_vdev_set_cfg: 2021: vap transmit called on
invalid interface
[ 1280.388498] wlan: [5109:I:ANY] ieee80211_mbo_vdetach: MBO terminated
[ 1280.388498]
[ 1280.388510] wlan: [5109:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1280.388510]
[ 1280.388689] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_del
_resp: mac: 16:0c:6b:44:ff:af vdevid: 1 Unable to find vdev
[ 1280.389445] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdevid: 984: Get MPSTA
: vdev is NULL
[ 1281.118959] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1281.118959]
[ 1281.382680] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1281.382680]
[ 1281.382681] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1281.382681]
[ 1281.476660] wlan: [2893:I:ANY] Skip bcst de-auth reason code 3, handled in VDEV
down
[ 1281.522539] device ath12 left promiscuous mode
[ 1281.522696] br-guest: port 6(ath12) entered disabled state
[ 1281.682770] wlan: [5283:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach b5e535c0:
if_num 40
[ 1281.682783] wlan: [5283:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interf
ace Node :40 of type:6
[ 1281.687980] wlan: [0:I:ANY] osif_nss_vdev_set_cfg: 2021: vap transmit called on
invalid interface
[ 1281.688413] wlan: [5283:I:ANY] ieee80211_mbo_vdetach: MBO terminated
[ 1281.688413]
[ 1281.688426] wlan: [5283:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1281.688426]
[ 1281.688605] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_del
_resp: mac: 1a:0c:6b:44:ff:af vdevid: 2 Unable to find vdev
[ 1281.689393] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdevid: 984: Get MPSTA
: vdev is NULL
[ 1282.114690] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1282.114690]
[ 1282.682361] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1282.682361]
[ 1282.682782] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1282.682782]
[ 1282.684365] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1282.684365]
[ 1282.792985] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 M
ax_mac_rings 1
[ 1282.793033] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 M
ax_mac_rings 1
```

```
[ 1282.793057] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 Max_mac_rings 1
[ 1282.793074] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 Max_mac_rings 1
[ 1282.863373] wlan: [5372:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach a6d65640: if_num 41
[ 1282.863389] wlan: [5372:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interface Node :41 of type:6
[ 1282.869111] wlan: [5372:I:ANY] ieee80211_mbo_vdetach: MBO terminated
[ 1282.869111] wlan: [5372:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1282.869130] wlan: [5372:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1282.869130] wlan: [5372:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1282.869307] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_delete_resp: mac: le:0c:6b:44:ff:af vdevid: 3 Unable to find vdev
[ 1282.870038] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdevid: 984: Get MPSTA: vdev is NULL
[ 1283.115075] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1283.115075] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1283.872382] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1283.872382] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1283.939466] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1283.939466] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1283.940026] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1283.940026] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1284.003743] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.003984] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.004100] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.004120] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.115964] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1284.115964] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1284.116085] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1284.116085] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1284.201454] wlan: [2893:I:ANY] Skip bcst de-auth reason code 3, handled in VDEV down
[ 1284.262737] device ath0 left promiscuous mode
[ 1284.262977] br-lan: port 7(ath0) entered disabled state
[ 1284.276509] wlan: [0:I:CMN_MLME] PSOC_0 VDEV_4 Sending bcst deauth and DELETE_ALL_PEER, clients: 12
[ 1284.279771] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.280251] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.282006] wlan: [6:I:ANY] son_bs_stats_update_cb: 1999: son_bs_stats_update_cb ctrl peer is null
[ 1284.282082] wlan: [6:I:ANY] son_bs_stats_update_cb: 1999: son_bs_stats_update_cb ctrl peer is null
[ 1284.302025] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.302063] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.302943] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.302998] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.303104] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.303122] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.304855] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.304927] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.305037] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.305056] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.305751] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.305813] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.305939] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1284.305962] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1284.330445] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 Max_mac_rings 1
[ 1284.330480] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 Max_mac_rings 1
[ 1284.333521] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 Max_mac_rings 1
[ 1284.333554] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 Max_mac_rings 1
[ 1284.412984] wlan: [5613:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach affd0500: if_num 42
[ 1284.412999] wlan: [5613:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interface Node :42 of type:6
[ 1284.418187] wlan: [0:I:ANY] osif_nss_vdev_set_cfg: 2021: vap transmit called on invalid interface
[ 1284.418656] wlan: [5613:I:ANY] ieee80211_mbo_vdetach: MBO terminated
```

```
[ 1284.418656]
[ 1284.418670] wlan: [5613:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1284.418670]
[ 1284.418822] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_del
_resp: mac: 10:0c:6b:44:ff:b0 vdevid: 4 Unable to find vdev
[ 1284.419478] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdevid: 984: Get MPSTA
: vdev is NULL
[ 1285.116755] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1285.116755]
[ 1285.411748] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.415207] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.415247] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.415257] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1285.415257]
[ 1285.415375] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.415394] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.415554] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1285.415554]
[ 1285.415595] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:298
[ 1285.415595]
[ 1285.415616] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1285.415616]
[ 1285.451026] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
2 Max_mac_rings 1
[ 1285.451061] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
1 Max_mac_rings 1
[ 1285.452120] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.452165] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.452190] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.452345] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.452391] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.453485] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.453520] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.453541] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.453652] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.453670] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.454497] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.454527] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.454555] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.454740] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.454764] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.455775] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.455810] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.455830] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.455958] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.455983] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.457215] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.457251] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.457272] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.457383] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.457406] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.458722] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.458776] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.458820] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.458937] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.458956] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.459786] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.459818] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.459848] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.459975] PF_BRIDGE: RTM_DELNEIGH with unknown ifindex
[ 1285.460001] PF_BRIDGE: RTM_DELNEIGH with invalid ifindex
[ 1285.464892] wlan: [2893:I:ANY] Skip bcast de-auth reason code 3, handled in VDEV
down
[ 1285.522419] device ath01 left promiscuous mode
[ 1285.522580] br-guest: port 7(ath01) entered disabled state
[ 1285.632831] wlan: [5776:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach b32b4600:
if_num 43
[ 1285.632847] wlan: [5776:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interf
ace Node :43 of type:6
[ 1285.638061] wlan: [0:I:ANY] osif_nss_vdev_set_cfg: 2021: vap transmit called on
invalid interface
[ 1285.638482] wlan: [5776:I:ANY] ieee80211_mbo_vdetach: MBO terminated
[ 1285.638482]
```



```
[ 1285.638496] wlan: [5776:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1285.638496]
[ 1285.638662] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_del
_resp: mac: 16:0c:6b:44:ff:b0 vdevid: 5 Unable to find vdev
[ 1285.639419] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdevid: 984: Get MPSTA
: vdev is NULL
[ 1286.116913] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1286.116913]
[ 1286.116962] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:299
[ 1286.116962]
[ 1286.116985] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1286.116985]
[ 1286.416406] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1286.416406]
[ 1286.416459] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:298
[ 1286.416459]
[ 1286.416481] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1286.416481]
[ 1286.652846] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 M
ax_mac_rings 1
[ 1286.652901] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 M
ax_mac_rings 1
[ 1286.763189] wlan: [5855:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach a8da5640:
if_num 44
[ 1286.763214] wlan: [5855:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interf
ace Node :44 of type:6
[ 1286.768789] wlan: [5855:I:ANY] ieee80211_mbo_vdetach: MBO terminated
[ 1286.768789]
[ 1286.768807] wlan: [5855:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1286.768807]
[ 1286.768967] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_del
_resp: mac: 1a:0c:6b:44:ff:b0 vdevid: 6 Unable to find vdev
[ 1286.769611] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdevid: 984: Get MPSTA
: vdev is NULL
[ 1287.117812] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1287.117812]
[ 1287.117864] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:299
[ 1287.117864]
[ 1287.117896] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1287.117896]
[ 1287.417107] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1287.417107]
[ 1287.417157] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:298
[ 1287.417157]
[ 1287.417179] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1287.417179]
[ 1287.762324] wlan: [5855:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 8
[ 1287.762542] wlan: [5855:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 2621
: ieee=58
[ 1287.832151] wlan: [2838:I:ANY] ol_acfg_handle_wifi_ioctl: 446: ol_acfg_handle_wif
i_ioctl: req->cmd=76 not valid for radio interface, it's for VAP
[ 1288.025960] wlan: [2893:I:ANY] Skip bcst de-auth reason code 3, handled in VDEV
down
[ 1288.117980] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:296
[ 1288.117980]
[ 1288.118047] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:299
[ 1288.118047]
[ 1288.118071] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1288.118071]
[ 1288.125490] device ath2 left promiscuous mode
[ 1288.125830] br-lan: port 8(ath2.4094) entered disabled state
[ 1288.139584] br-guest: port 8(ath2.4093) entered disabled state
[ 1288.168888] device ath2.4093 left promiscuous mode
[ 1288.168921] br-guest: port 8(ath2.4093) entered disabled state
[ 1288.171433] device ath2.4094 left promiscuous mode
[ 1288.171461] br-lan: port 8(ath2.4094) entered disabled state
[ 1288.233248] wlan: [6110:I:ANY] osif_nss_ol_vap_delete: 1856: vap detach b974b5c0:
if_num 45
[ 1288.233271] wlan: [6110:I:ANY] osif_nss_vdev_detach: 1633: Dealloc Dynamic interf
ace Node :45 of type:6
[ 1288.238468] wlan: [0:I:ANY] osif_nss_vdev_set_cfg: 2021: vap transmit called on
invalid interface
[ 1288.238863] wlan: [6110:I:ANY] ieee80211_mbo_vdetach: MBO terminated
```

```
[ 1288.238863]
[ 1288.238874] wlan: [6110:I:ANY] ieee80211_oce_vdetach: OCE terminated
[ 1288.238874]
[ 1288.239014] wlan: [0:I:ANY] ol_peer_delete_response_event_handler: 2879: peer_del
_resp: mac: 10:0c:6b:44:ff:b1 vdev: 7 Unable to find vdev
[ 1288.239730] wlan: [0:I:ANY] osif_nss_wifili_vdev_get_mpsta_vdev: 984: Get MPSTA
: vdev is NULL
[ 1288.417432] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1288.417432]
[ 1288.417484] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1288.417484]
[ 1288.417507] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1288.417507]
[ 1288.417528] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1288.417528]
[ 1289.118611] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1289.118611]
[ 1289.118669] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1289.118669]
[ 1289.118693] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1289.118693]
[ 1289.118712] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1289.118712]
[ 1289.232585] wlan: [6110:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 11
[ 1289.232886] wlan: [6110:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 2621
: ieee=106
[ 1289.232894] wlan: [6110:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 2621
: ieee=122
[ 1289.233252] wlan: [6110:I:ANY] ol_ath_soc_stop: 10273: Suspending Target soc=b59
c0500
[ 1289.233262] wlan: [6110:I:ANY] wlan_pdev_operation: 830: wlan_pdev_operation: dis
able_target_intr val is 1
[ 1289.233291] wlan: [6110:I:ANY] wlan_pdev_operation: 830: wlan_pdev_operation: dis
able_target_intr val is 1
[ 1289.233309] wlan: [6110:I:ANY] wlan_pdev_operation: 830: wlan_pdev_operation: dis
able_target_intr val is 1
[ 1289.233327] wlan: [6110:I:ANY] ol_ath_soc_stop: 10276: ol_ath_soc_stop: waiting f
or target paused event from target
[ 1289.233335] wlan: [6110:I:ANY] ol_ath_soc_stop: 10296: nss-wifi: detach soc->soc_
idx: 0 - 100 delay
[ 1289.233346] wlan: [6110:E:NSS] [nss-wifili]: sending soc stop message to NSS
[ 1289.418213] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1289.418213]
[ 1289.418278] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1289.418278]
[ 1289.418302] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1289.418302]
[ 1289.418322] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1289.418322]
[ 1289.743797] wlan: [6110:E:NSS] [nss-wifili]: calling pdev de-attach with id 0
[ 1289.748202] wlan: [6110:E:NSS] [nss-wifili]: calling pdev de-attach with id 1
[ 1289.752622] wlan: [6110:E:NSS] [nss-wifili]: calling pdev de-attach with id 2
[ 1289.778235] wlan: [6110:E:NSS] nss-wifili: Free Host Pool Memory
[ 1289.778263] wlan: [6110:I:ANY] ol_ath_soc_stop: 10302: disable dp interrupts:: so
c: b5e48000
[ 1289.823562] wlan: [6110:E:CFR] tgt_cfr_deinit_pdev: 124: Error occurred with exit
code 16
[ 1289.823562]
[ 1289.823579] wlan: [6110:E:CFR] cfr_deinitialize_pdev: 157: cfr_deinitialize_pdev
status=16
[ 1289.823579]
[ 1289.836025] wlan: [6110:E:CFR] tgt_cfr_deinit_pdev: 124: Error occurred with exit
code 16
[ 1289.836025]
[ 1289.836042] wlan: [6110:E:CFR] cfr_deinitialize_pdev: 157: cfr_deinitialize_pdev
status=16
[ 1289.836042]
[ 1289.839835] cnss: QMI WLFW service disconnected, state: 0x6
[ 1289.839886] wlan: [6110:I:ANY] ol_ath_wifi_ssr: 256: ol_ath_wifi_ssr: SSR event 0
bus_type 1
[ 1289.839903] wlan: [6110:I:ANY] ol_ath_wifi_ssr: 311: nss-wifi: soc_stop soc->soc_
idx: 0
[ 1289.839910] wlan: [6110:E:NSS] [nss-wifili]: stop ERROR - Null nss context
```

```
[ 1289.866016] remoteproc remoteproc0: stopped remote processor cd00000.qcom_q6v5_wc
ss
[ 1289.866053] wlan: [6110:I:ANY] ol_ath_wifi_ssr: 256: ol_ath_wifi_ssr: SSR event 1
bus_type 1
[ 1289.931800] wlan: [2838:I:ANY] ol_acfg_handle_wifi_ioctl: 446: ol_acfg_handle_wif
i_ioctl: req->cmd=76 not valid for radio interface, it's for VAP
[ 1290.119821] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1290.119821]
[ 1290.119886] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1290.119886]
[ 1290.119919] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1290.119919]
[ 1290.119947] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1290.119947]
[ 1290.419086] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1290.419086]
[ 1290.419174] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1290.419174]
[ 1290.419217] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1290.419217]
[ 1290.419244] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1290.419244]
[ 1291.120816] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1291.120816]
[ 1291.120871] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1291.120871]
[ 1291.120894] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1291.120894]
[ 1291.120894] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1291.120914]
[ 1291.120914] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1291.120914]
[ 1291.422017] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1291.422017]
[ 1291.422086] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1291.422086]
[ 1291.422086] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1291.422113]
[ 1291.422113] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1291.422113]
[ 1291.422135] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1291.422135]
[ 1291.963397] wlan: [7480:I:ANY] ol_ath_ucfg_setparam: 215: Starting the target bef
ore sending the command
[ 1291.963429] wlan: [7480:I:ANY] ol_ath_wifi_ssr: 256: ol_ath_wifi_ssr: SSR event 2
bus_type 1
[ 1291.963448] remoteproc remoteproc0: powering up cd00000.qcom_q6v5_wcss
[ 1291.963698] remoteproc remoteproc0: Booting fw image IPQ8074/q6_fw.mdt, size 668
[ 1292.121419] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1292.121419]
[ 1292.121469] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1292.121469]
[ 1292.121491] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1292.121491]
[ 1292.121511] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1292.121511]
[ 1292.321389] remoteproc remoteproc0: remote processor cd00000.qcom_q6v5_wcss is no
w up
[ 1292.321463] wlan: [7480:I:ANY] ol_ath_wifi_ssr: 256: ol_ath_wifi_ssr: SSR event 3
bus_type 1
[ 1292.321483] wlan: [7480:I:ANY] ol_ath_target_start: 10899: subsystem_get success
[ 1292.321492] wlan: [7480:I:ANY] ol_ath_check_fw_ready: 614: Waiting for FW ready d
evice fffe
[ 1292.321910] rpmsg_dev_probe: No pm domain
[ 1292.322442] rpmsg_dev_probe: No pm domain
[ 1292.323297] cnss: QMI WLFW service connected, state: 0x1
[ 1292.323555] cnss: device_id : 65534 mem mode : [0]
[ 1292.324644] cnss: Target capability: chip_id: 0x0, chip_family: 0x0, board_id: 0x
ff, soc_id: 0xffffffff, fw_version: 0x220a04a5, fw_build_timestamp: 2021-01-20 23:31
, otp_version: 0x0 eeprom caldata_read timeout 0s
[ 1292.324676] cnss: Downloading BDF: bdwlan.bin, size: 64
[ 1292.324683] cnss: Boardid from dts:213,FW:ff
[ 1292.325104] cnss: BDF location : 0x4b0c0000
[ 1292.325109] cnss: BDF IPQ8074/bdwlan.b213 size 131072
[ 1292.325407] cnss: Downloading BDF: caldata.bin, size: 64
[ 1292.325777] cnss: per device BDF location : 0x4b0e0000
[ 1292.325843] cnss: CALDATA IPQ8074/caldata.bin size 131072 offset 0x20000
```

```
[ 1292.421695] wlan: [7480:I:ANY] ol_ath_check_fw_ready: 624: FW ready received for
device fffe
[ 1292.422117] wlan: [7480:I:ANY] pld_ahb_wlan_enable: 699: cnss_mode: Mission mode
[ 1292.422853] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1292.422853]
[ 1292.422900] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1292.422900]
[ 1292.422921] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1292.422921]
[ 1292.422940] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1292.422940]
[ 1292.431966] wlan: [7480:I:ANY] qca_napi_create: 364: qca_napi_create: napi instan
ce 0 created on pipe 4
[ 1292.432075] wlan: [7480:I:ANY] htc_wmi_init: 6200: htc_wmi_init() HT Create . b33
81040
[ 1292.432082] wlan: [7480:I:ANY] htc_wmi_init: 6207: htc_wmi_init() Skipping BMI Do
ne.
[ 1292.432090] wlan: [7480:I:ANY] htc_wmi_init: 6264: [htc_wmi_init:6264] host_enabl
e 0 nss_nwifi_offload 0
[ 1292.435264] wlan: [7480:I:ANY] ol_target_init_complete: 6386: CDP soc attach succ
ess
[ 1292.435274] wlan: [7480:I:ANY] ol_target_init_complete: 6393: Soc attach success
NSS config 0
[ 1292.435331] wlan: [7480:I:ANY] htc_set_async_ep: 428: htc_set_async_ep: htc_handl
e b3381040, ep 2, value 1
[ 1292.435384] wlan: [7480:I:ANY] htc_set_async_ep: 428: htc_set_async_ep: htc_handl
e b3381040, ep 3, value 1
[ 1292.435435] wlan: [7480:I:ANY] htc_set_async_ep: 428: htc_set_async_ep: htc_handl
e b3381040, ep 4, value 1
[ 1292.436183] wlan: [130:I:TIF] HE CAP Info = 1a08010d
[ 1292.436189] wlan: [130:I:TIF] Num HW modes = 2
[ 1292.436194] wlan: [130:I:TIF] Num PHY = 3
[ 1292.436203] wlan: [130:I:TIF] Preferred HW Mode = 4 Num Radios = 3
[ 1292.436212] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1779: Adding llax regul
atory modes,
[ 1292.436220] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1783: phy_id = 0 wirel
ess modes = 391f9001
[ 1292.436226] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1779: Adding llax regul
atory modes,
[ 1292.436233] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1783: phy_id = 1 wirel
ess modes = 680680c
[ 1292.436239] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1779: Adding llax regul
atory modes,
[ 1292.436246] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1783: phy_id = 2 wirel
ess modes = 391f9001
[ 1292.436254] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1806: hw_mode_id = 1 ph
y_id = 0 wireless modes = 397f9001
[ 1292.436261] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1806: hw_mode_id = 1 ph
y_id = 1 wireless modes = 680688c
[ 1292.436268] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1806: hw_mode_id = 4 ph
y_id = 0 wireless modes = 391f9001
[ 1292.436276] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1806: hw_mode_id = 4 ph
y_id = 1 wireless modes = 680688c
[ 1292.436283] wlan: [130:I:TIF] init_deinit_add_llax_modes: 1806: hw_mode_id = 4 ph
y_id = 2 wireless modes = 391f9001
[ 1292.436334] wlan: [130:I:ANY] init_deinit_update_pdev_tgt_info: 1347: pdev id:0 w
mi_handle:ba069d40
[ 1292.442712] wlan: [130:I:ANY] init_deinit_update_pdev_tgt_info: 1403: Pdev = 0 Nu
mber of peers = 529 vdevs = 17
[ 1292.442722] wlan: [130:I:TIF] init_deinit_update_pdev_tgt_info: 1406: CDP PDEV AT
TACH success
[ 1292.442734] wlan: [130:I:ANY] init_deinit_update_pdev_tgt_info: 1347: pdev id:1 w
mi_handle:b4f0f600
[ 1292.453747] wlan: [130:I:ANY] init_deinit_update_pdev_tgt_info: 1403: Pdev = 1 Nu
mber of peers = 529 vdevs = 17
[ 1292.453759] wlan: [130:I:TIF] init_deinit_update_pdev_tgt_info: 1406: CDP PDEV AT
TACH success
[ 1292.453769] wlan: [130:I:ANY] init_deinit_update_pdev_tgt_info: 1347: pdev id:2 w
mi_handle:b4f0f180
[ 1292.468902] wlan: [130:I:ANY] init_deinit_update_pdev_tgt_info: 1403: Pdev = 2 Nu
mber of peers = 529 vdevs = 17
[ 1292.468915] wlan: [130:I:TIF] init_deinit_update_pdev_tgt_info: 1406: CDP PDEV AT
TACH success
```

```
[ 1292.569553] wlan: [130:I:ANY] copy_fw_abi_version_tlv: 6960: copy_fw_abi_version_tlv: INIT_CMD version: 1, 0, 0x5f414351, 0x4c4d, 0x0, 0x0
[ 1292.820270] wlan: [130:I:ANY] ready_extract_init_status_tlv: 9002: ready_extract_init_status_tlv:0
[ 1292.820287] wlan: [130:E:TIF] init_deinit_ready_event_handler: 500: Host Requested 1587 peers. FW Supports 1568 peers
[ 1292.820300] wlan: [130:I:ANY] dp_peer_map_attach_wifi3: 9799: dp_peer_map_attach_wifi3 max_peers 1636, max_ast_index: 4112
[ 1292.820300]
[ 1292.820584] wlan: [7480:I:ANY] ol_ath_connect_htc: 1216: WMI is ready
[ 1292.877720] wlan: [7480:E:TIF] target_if_lro_hash_config: 254: pdev with id 0 is NULL
[ 1292.884084] wlan: [7480:E:TIF] target_if_lro_hash_config: 254: pdev with id 1 is NULL
[ 1292.892134] wlan: [7480:E:TIF] target_if_lro_hash_config: 254: pdev with id 2 is NULL
[ 1292.892444] wlan: [7480:I:ANY] ol_ath_soc_start: 10565: Skip txrx_pdev_attach_target
[ 1292.892451] wlan: [7480:I:ANY] ol_ath_soc_start: 10603: BURSTING enabled by default
[ 1292.893011] wlan: [0:I:ANY] ol_ath_twt_enable_complete_event_handler: 14717: twt enabled.
[ 1292.893011]
[ 1292.898485] wlan: [7480:I:ANY] ol_ath_stats_attach: 2275: periodic_chan_stats: 1
[ 1292.899097] wlan: [7480:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 8
[ 1292.899324] wlan: [7480:I:ANY] ol_ath_configure_cong_ctrl_max_msdu: 3848: pdev_idx = 0 tx_desc_limit = 24576
[ 1292.899358] wlan: [7480:I:ANY] dp_lag_pdev_set_primary_radio: 55: pdev(a7c6eac4) is primary 1
[ 1292.899386] wlan: [7480:I:ANY] ol_ath_soc_start: 10565: Skip txrx_pdev_attach_target
[ 1292.899392] wlan: [7480:I:ANY] ol_ath_soc_start: 10603: BURSTING enabled by default
[ 1292.901075] wlan: [0:I:ANY] ol_ath_twt_enable_complete_event_handler: 14717: twt enabled.
[ 1292.901075]
[ 1292.905445] wlan: [7480:I:ANY] ol_ath_stats_attach: 2275: periodic_chan_stats: 1
[ 1292.905790] wlan: [7480:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 11
[ 1292.906021] wlan: [7480:I:ANY] ol_ath_configure_cong_ctrl_max_msdu: 3848: pdev_idx = 1 tx_desc_limit = 24576
[ 1292.906044] wlan: [7480:I:ANY] dp_lag_pdev_set_primary_radio: 55: pdev(a7c6e644) is primary 0
[ 1292.906070] wlan: [7480:I:ANY] ol_ath_soc_start: 10565: Skip txrx_pdev_attach_target
[ 1292.906077] wlan: [7480:I:ANY] ol_ath_soc_start: 10603: BURSTING enabled by default
[ 1292.907557] wlan: [0:I:ANY] ol_ath_twt_enable_complete_event_handler: 14717: twt enabled.
[ 1292.907557]
[ 1292.911323] wlan: [7480:I:ANY] ol_ath_stats_attach: 2275: periodic_chan_stats: 1
[ 1292.912193] wlan: [7480:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 17
[ 1292.912429] wlan: [7480:I:ANY] ol_ath_configure_cong_ctrl_max_msdu: 3848: pdev_idx = 2 tx_desc_limit = 24576
[ 1292.912452] wlan: [7480:I:ANY] dp_lag_pdev_set_primary_radio: 55: pdev(a7c6d444) is primary 0
[ 1292.912495] wlan: [7480:I:Dynamic Mode Change] ol_ath_check_and_reconfig_hw_mode: 3817: Running with HW mode = 4
[ 1292.914752] wlan: [7480:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 13
[ 1292.914853] wlan: [7480:I:ANY] number of channels: 2G = 13 5G = 0, 6G = 0
[ 1293.124006] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1293.124006]
[ 1293.124061] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1293.124061]
[ 1293.124084] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1293.124084]
[ 1293.124105] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1293.124105]
[ 1293.175139] wlan: [7612:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 Max_mac_rings 1
[ 1293.175198] wlan: [7612:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 Max_mac_rings 1
[ 1293.210074] wlan: [7630:I:ANY] wlan_cfg80211_set_hwaddr: 6591: wlan_cfg80211_set_hwaddr :10:0c:6b:44:ff:af ret: 0
```

```
[ 1293.251256] wlan: [7645:I:ANY] ol_ath_set_config_param: 1664: set TXBF_SND_PERIOD
: value 100 wmi_status 0
[ 1293.377001] wlan: [0:I:ANY] dp_lag_soc_enable: 102: pdev(a7c6e644) Enabling DBDC
Repeater 0
[ 1293.377115] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1293.377125] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1293.377132] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1293.377139] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1293.425438] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1293.425438]
[ 1293.425499] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1293.425499]
[ 1293.425541] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1293.425541]
[ 1293.425573] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1293.425573]
[ 1293.468470] wlan: [0:I:ANY] ol_ath_set_config_param: 2416: Disconnect_timeout val
ue: 10
[ 1293.513268] wlan: [0:I:ANY] ol_ath_set_config_param: 2422: Reconfiguration_timeou
t value:60
[ 1294.031055] wlan: [8066:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary m
ode 6 for interface: ath1 : clone params: 0x00000001
[ 1294.031131] wlan: [8066:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 10:0c:6b:
44:ff:af
[ 1294.031210] wlan: [8066:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmod
e=IEEE80211_M_HOSTAP, flags=0x1
[ 1294.031210]
[ 1294.031504] wlan: [8066:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1294.031542] wlan: [8066:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfee
:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_bf
er:0
[ 1294.031549] wlan: [8066:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1294.031567] wlan: [8066:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT sou
nding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1294.031941] wlan: [8066:I:ANY] MBO Initialized
[ 1294.031951] wlan: [8066:I:ANY] OCE Initialized
[ 1294.031979] wlan: [8066:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VAP
create IF 49 nss_id -1
[ 1294.031991] wlan: [8066:I:ANY] NSS radio_if 47
[ 1294.032090] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1294.032109] wlan: [8066:I:ANY] osif_nss_ol_vap_create: 1393: vap create b022c600
: if num 49
[ 1294.032488] wlan: [8066:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:1
|TSO:1|LRO:0
[ 1294.032496] wlan: [8066:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1294.035396] wlan: [8066:I:ANY] VAP device ath1 created osifp: (b022c600) os_if: (
af690000)
[ 1294.124812] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1294.124812]
[ 1294.124865] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1294.124865]
[ 1294.124888] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1294.124888]
[ 1294.124908] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1294.124908]
[ 1294.426948] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1294.426948]
[ 1294.427003] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1294.427003]
[ 1294.427026] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1294.427026]
[ 1294.427047] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1294.427047]
[ 1295.127416] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1295.127416]
[ 1295.127478] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1295.127478]
[ 1295.127510] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
```

```
[ 1295.127510]
[ 1295.127543] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1295.127543]
[ 1295.293074] device ath1 entered promiscuous mode
[ 1295.295741] br-lan: port 5(ath1) entered listening state
[ 1295.295831] br-lan: port 5(ath1) entered listening state
[ 1295.308809] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3709: vap-0(ath1):ACS Params
[ 1295.308826] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3712: ht_enabled:1|ht40_enab
led:0|vht_enabled:1|hw_mode:29|chwidth:20|
[ 1295.308839] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS
started: vap:0xaf690000
[ 1295.427742] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1295.427742]
[ 1295.427818] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1295.427818]
[ 1295.427853] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1295.427853]
[ 1295.427878] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1295.427878]
[ 1295.598950] wlan: [8841:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fra
gmentation with HT mode NOT ALLOWED!!
[ 1295.637879] wlan: [8866:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary m
ode 6 for interface: ath11 : clone params: 0x00000001
[ 1295.637972] wlan: [8866:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 16:0c:6b:
44:ff:af
[ 1295.638088] wlan: [8866:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmod
e=IEEE80211_M_HOSTAP, flags=0x1
[ 1295.638088]
[ 1295.638373] wlan: [8866:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1295.638424] wlan: [8866:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfee
:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_bf
er:0
[ 1295.638431] wlan: [8866:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1295.638456] wlan: [8866:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT sou
nding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1295.638545] wlan: [8866:I:ANY] MBO Initialized
[ 1295.638554] wlan: [8866:I:ANY] OCE Initialized
[ 1295.638590] wlan: [8866:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VAP
create IF 50 nss_id -1
[ 1295.638599] wlan: [8866:I:ANY] NSS radio_if 47
[ 1295.638679] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1295.638703] wlan: [8866:I:ANY] osif_nss_ol_vap_create: 1393: vap create b3ac9540
: if num 50
[ 1295.639053] wlan: [8866:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:1
|TSO:1|LRO:0
[ 1295.639059] wlan: [8866:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1295.642274] wlan: [8866:I:ANY] VAP device ath11 created osifp: (b3ac9540) os_if:
(b4f98000)
[ 1295.659428] device ath11.4093 entered promiscuous mode
[ 1295.659443] device ath11 entered promiscuous mode
[ 1295.659700] br-guest: port 5(ath11.4093) entered forwarding state
[ 1295.659766] br-guest: port 5(ath11.4093) entered forwarding state
[ 1295.678650] device ath11.4094 entered promiscuous mode
[ 1295.679234] br-lan: port 6(ath11.4094) entered listening state
[ 1295.679294] br-lan: port 6(ath11.4094) entered listening state
[ 1296.128279] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1296.128279]
[ 1296.128334] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1296.128334]
[ 1296.128356] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1296.128356]
[ 1296.128375] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1296.128375]
[ 1296.428788] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1296.428788]
[ 1296.428841] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1296.428841]
[ 1296.428863] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1296.428863]
[ 1296.428883] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1296.428883]
[ 1296.948762] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3709: vap-1(ath11):ACS Param
```

```
S
[ 1296.948779] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3712: ht_enabled:1|ht40_enabled:0|vht_enabled:1|hw_mode:29|chwidth:20|
[ 1296.948793] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS started: vap:0xb4f98000
[ 1297.011262] wlan: [9426:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fragmentation with HT mode NOT ALLOWED!!
[ 1297.011288] wlan: [9426:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fragmentation with HT mode NOT ALLOWED!!
[ 1297.043632] wlan: [9438:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary mode 6 for interface: ath12 : clone params: 0x00000001
[ 1297.043711] wlan: [9438:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 1a:0c:6b:44:ff:af
[ 1297.043788] wlan: [9438:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmode=IEEE80211_M_HOSTAP, flags=0x1
[ 1297.043788]
[ 1297.044021] wlan: [9438:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1297.044067] wlan: [9438:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfee:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_bfer:0
[ 1297.044074] wlan: [9438:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1297.044091] wlan: [9438:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT sounding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Trigged
[ 1297.044172] wlan: [9438:I:ANY] MBO Initialized
[ 1297.044179] wlan: [9438:I:ANY] OCE Initialized
[ 1297.044215] wlan: [9438:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VAP create IF 51 nss_id -1
[ 1297.044224] wlan: [9438:I:ANY] NSS radio_if 47
[ 1297.044276] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration success: 0
[ 1297.044293] wlan: [9438:I:ANY] osif_nss_ol_vap_create: 1393: vap create a909d640 : if_num 51
[ 1297.044643] wlan: [9438:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:1|TSO:1|LRO:0
[ 1297.044650] wlan: [9438:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1297.049559] wlan: [9438:I:ANY] VAP device ath12 created osifp: (a909d640) os_if: (aa0d0000)
[ 1297.128847] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1297.128847]
[ 1297.128897] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1297.128897]
[ 1297.128927] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1297.128927]
[ 1297.128948] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1297.128948]
[ 1297.291708] br-lan: port 5(ath1) entered learning state
[ 1297.429250] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1297.429250]
[ 1297.429285] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1297.429285]
[ 1297.429311] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1297.429311]
[ 1297.651687] br-guest: port 5(ath11.4093) entered forwarding state
[ 1297.671705] br-lan: port 6(ath11.4094) entered learning state
[ 1298.129557] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1298.129557]
[ 1298.129612] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1298.129612]
[ 1298.129634] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1298.129634]
[ 1298.129653] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1298.129653]
[ 1298.196712] device ath12 entered promiscuous mode
[ 1298.197327] br-guest: port 6(ath12) entered forwarding state
[ 1298.197411] br-guest: port 6(ath12) entered forwarding state
[ 1298.199300] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3709: vap-2(ath12):ACS Param
S
[ 1298.199317] wlan: [2893:I:ANY] wlan_cfg80211_do_acs: 3712: ht_enabled:1|ht40_enabled:0|vht_enabled:1|hw_mode:29|chwidth:20|
[ 1298.199332] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS started: vap:0xaa0d0000
[ 1298.429789] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1298.429789]
```



```
[ 1298.429849] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1298.429849]
[ 1298.429881] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1298.429881]
[ 1298.454861] wlan: [10000:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fragmentation with HT mode NOT ALLOWED!!
[ 1298.454875] wlan: [10000:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fragmentation with HT mode NOT ALLOWED!!
[ 1298.454883] wlan: [10000:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fragmentation with HT mode NOT ALLOWED!!
[ 1298.489811] wlan: [10015:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary mode 6 for interface: ath13 : clone params: 0x00005001
[ 1298.489878] wlan: [10015:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 1e:0c:6b:44:ff:af
[ 1298.489961] wlan: [10015:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ee0500, opmode=IEEE80211_M_HOSTAP, flags=0x5001
[ 1298.489961]
[ 1298.490200] wlan: [10015:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1298.490252] wlan: [10015:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_bfer:0
[ 1298.490259] wlan: [10015:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1298.490278] wlan: [10015:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT sounding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Trigged
[ 1298.490354] wlan: [10015:I:ANY] MBO Initialized
[ 1298.490362] wlan: [10015:I:ANY] OCE Initialized
[ 1298.490396] wlan: [10015:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VAP create IF 52 nss_id -1
[ 1298.490405] wlan: [10015:I:ANY] NSS radio_if 47
[ 1298.490444] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration success: 0
[ 1298.490463] wlan: [10015:I:ANY] osif_nss_ol_vap_create: 1393: vap create ada435c0 : if_num 52
[ 1298.490809] wlan: [10015:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:1|TSO:1|LRO:0
[ 1298.490816] wlan: [10015:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1298.493969] wlan: [10015:I:ANY] VAP device ath13 created osifp: (ada435c0) os_if: (b3e48000)
[ 1298.723505] wlan: [10099:I:ANY] DES SSID SET=SM_0
[ 1299.130388] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1299.130388]
[ 1299.130443] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1299.130443]
[ 1299.130466] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1299.130466]
[ 1299.130487] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1299.130487]
[ 1299.291709] br-lan: topology change detected, propagating
[ 1299.291728] br-lan: port 5(ath1) entered forwarding state
[ 1299.430262] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1299.430262]
[ 1299.430311] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1299.430311]
[ 1299.430335] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1299.430335]
[ 1299.671743] br-lan: topology change detected, propagating
[ 1299.671762] br-lan: port 6(ath11.4094) entered forwarding state
[ 1299.758730] wlan: [2893:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS started: vap:0xb3e48000
[ 1299.985091] wlan: [10592:I:ANY] ieee80211_autoselect_infra_bss_channel: 5031: ACS started: vap:0xb3e48000
[ 1300.130877] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1300.130877]
[ 1300.130950] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1300.130950]
[ 1300.130984] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1300.130984]
[ 1300.131012] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1300.131012]
[ 1300.191696] br-guest: port 6(ath12) entered forwarding state
[ 1300.431272] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1300.431272]
[ 1300.431303] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
```

```
[ 1300.431303]
[ 1300.431324] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1300.431324]
[ 1301.132056] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1301.132056]
[ 1301.132112] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1301.132112]
[ 1301.132135] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1301.132135]
[ 1301.132157] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1301.132157]
[ 1301.395355] wlan: [11516:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 8
[ 1301.395594] wlan: [11516:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=58
[ 1301.396287] wlan: [11516:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 8
[ 1301.396403] wlan: [11516:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=58
[ 1301.396428] wlan: [11516:I:ANY] number of channels: 2G = 0 5G = 8, 6G = 0
[ 1301.398174] wlan: [2838:I:ANY] ol_acfg_handle_wifi_ioctl: 446: ol_acfg_handle_wif
i_ioctl: req->cmd=76 not valid for radio interface, it's for VAP
[ 1301.432947] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1301.432947]
[ 1301.432977] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1301.432977]
[ 1301.433001] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1301.433001]
[ 1301.631569] wlan: [11605:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
2 Max_mac_rings 1
[ 1301.631630] wlan: [11605:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
1 Max_mac_rings 1
[ 1301.670447] wlan: [11624:I:ANY] wlan_cfg80211_set_hwaddr: 6591: wlan_cfg80211_set
_hwaddr :10:0c:6b:44:ff:b0 ret: 0
[ 1301.718178] wlan: [11634:I:ANY] ol_ath_set_config_param: 1664: set TXBF_SND_PERIO
D: value 100 wmi_status 0
[ 1301.845578] wlan: [0:I:ANY] dp_lag_soc_enable: 102: pdev(a7c6eac4) Enabling DBDC
Repeater 0
[ 1301.845672] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1301.845682] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1301.845689] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1301.845696] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1301.929544] wlan: [1827:I:ANY] vap-0(ath1): ACS result PCH 2 freq 2417, SCH 6 fre
q 2437, hw_mode 1 chwidth 40, vht_seg0 4 freq 2427, vht_seg1 0 freq 0
[ 1301.929647] wlan: [1827:I:ANY] vap-1(ath11): ACS result PCH 2 freq 2417, SCH 6 fr
eq 2437, hw_mode 1 chwidth 40, vht_seg0 4 freq 2427, vht_seg1 0 freq 0
[ 1301.929734] wlan: [1827:I:ANY] vap-2(ath12): ACS result PCH 2 freq 2417, SCH 6 fr
eq 2437, hw_mode 1 chwidth 40, vht_seg0 4 freq 2427, vht_seg1 0 freq 0
[ 1301.930005] wlan: [1827:I:ANY] vdev[3]: Mgt Rate:1000(kbps)
[ 1301.930028] wlan: [1827:I:ANY] ieee80211_acs_scan_evhandler: 4759: lock held dura
tion: 1(ms)
[ 1301.939433] wlan: [0:I:ANY] ol_ath_set_config_param: 2416: Disconnect_timeout val
ue: 10
[ 1301.952319] wlan: [2893:I:ANY] DES SSID SET=reality_optout
[ 1301.952343] wlan: [2893:I:ANY] wlan_cfg80211_chan_to_phymode: 1239: wlan_cfg80211
_chan_to_phymode: band:0 width: 2 channel_cfreq: 2417 center_freq1: 2427 chandef.cen
ter_freq2: 0 flags: 0
[ 1301.952468] wlan: [2893:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1301.952468] Channel is configured already!!
[ 1301.976003] wlan: [2893:I:ANY] DES SSID SET=NETGEAR_ORBI_hidden43
[ 1301.976021] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
26
[ 1301.976141] wlan: [2893:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1301.976141] Channel is configured already!!
[ 1301.994107] wlan: [0:I:ANY] ol_ath_set_config_param: 2422: Reconfiguration_timeou
t value:60
[ 1302.006371] wlan: [2893:I:ANY] DES SSID SET=pocket-reality_optout
[ 1302.006387] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
26
[ 1302.006505] wlan: [2893:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1302.006505] Channel is configured already!!
```

```
[ 1302.043995] wlan: [0:I:CMN_MLME] vdev[3] ieee chan:2 freq:2417
[ 1302.044155] wlan: [0:I:ANY] vdev[3]: Mgt Rate:1000(kbps)
[ 1302.044193] wlan: [0:I:ANY] vdev[3]: Mgt Rate:1000(kbps)
[ 1302.074095] wlan: [0:I:CMN_MLME] vdev[0] ieee chan:2 freq:2417
[ 1302.074418] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1302.074418] FD Interval should be a factor of BI.
[ 1302.074418] Disabling FD
[ 1302.074418]
[ 1302.074636] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1302.074636] FD Interval should be a factor of BI.
[ 1302.074636] Disabling FD
[ 1302.074636]
[ 1302.074684] wlan: [0:I:ANY] vdev[0]: Mgt Rate:1000(kbps)
[ 1302.074723] wlan: [0:I:ANY] vdev[0]: Mgt Rate:1000(kbps)
[ 1302.074803] wlan: [0:I:CMN_MLME] vdev[1] ieee chan:2 freq:2417
[ 1302.075026] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1302.075026] FD Interval should be a factor of BI.
[ 1302.075026] Disabling FD
[ 1302.075026]
[ 1302.075165] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1302.075165] FD Interval should be a factor of BI.
[ 1302.075165] Disabling FD
[ 1302.075165]
[ 1302.075197] wlan: [0:I:ANY] vdev[1]: Mgt Rate:1000(kbps)
[ 1302.075231] wlan: [0:I:ANY] vdev[1]: Mgt Rate:1000(kbps)
[ 1302.075294] wlan: [0:I:CMN_MLME] vdev[2] ieee chan:2 freq:2417
[ 1302.075484] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1302.075484] FD Interval should be a factor of BI.
[ 1302.075484] Disabling FD
[ 1302.075484]
[ 1302.075617] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1302.075617] FD Interval should be a factor of BI.
[ 1302.075617] Disabling FD
[ 1302.075617]
[ 1302.075650] wlan: [0:I:ANY] vdev[2]: Mgt Rate:1000(kbps)
[ 1302.075682] wlan: [0:I:ANY] vdev[2]: Mgt Rate:1000(kbps)
[ 1302.132518] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1302.132518]
[ 1302.132561] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1302.132561]
[ 1302.132587] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1302.132587]
[ 1302.433569] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1302.433569]
[ 1302.433605] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1302.433605]
[ 1302.433640] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1302.433640]
[ 1302.457274] wlan: [11981:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath0 : clone params: 0x00000001
[ 1302.457369] wlan: [11981:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 10:0c:6b
:44:ff:b0
[ 1302.457485] wlan: [11981:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ea0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x1
[ 1302.457485]
[ 1302.460073] wlan: [11981:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1302.460130] wlan: [11981:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1302.460137] wlan: [11981:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1302.460156] wlan: [11981:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1302.460237] wlan: [11981:I:ANY] MBO Initialized
[ 1302.460246] wlan: [11981:I:ANY] OCE Initialized
[ 1302.460276] wlan: [11981:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 53 nss_id -1
[ 1302.460286] wlan: [11981:I:ANY] NSS radio_if 46
```

```
[ 1302.460385] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1302.460407] wlan: [11981:I:ANY] osif_nss_ol_vap_create: 1393: vap create b197c600
: if_num 53
[ 1302.460771] wlan: [11981:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1302.460779] wlan: [11981:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1302.463839] wlan: [11981:I:ANY] VAP device ath0 created osifp: (b197c600) os_if:
(b38d0000)
[ 1303.133204] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1303.133204]
[ 1303.133236] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1303.133236]
[ 1303.133256] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1303.133256]
[ 1303.434465] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1303.434465]
[ 1303.434499] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1303.434499]
[ 1303.434521] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1303.434521]
[ 1303.567071] device ath0 entered promiscuous mode
[ 1303.567342] br-lan: port 7(ath0) entered listening state
[ 1303.567408] br-lan: port 7(ath0) entered listening state
[ 1303.586589] wlan: [2893:I:ANY] DES SSID SET=reality_optout
[ 1303.586606] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
30
[ 1303.587002] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1303.760968] wlan: [0:I:CMN MLME] vdev[4] ieee chan:40 freq:5200
[ 1303.761266] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1303.761266] FD Interval should be a factor of BI.
[ 1303.761266] Disabling FD
[ 1303.761266]
[ 1303.761450] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1303.761450] FD Interval should be a factor of BI.
[ 1303.761450] Disabling FD
[ 1303.761450]
[ 1303.761497] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1303.761533] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1303.869212] wlan: [12520:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1303.881905] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1303.899158] wlan: [0:I:CMN MLME] vdev[4] ieee chan:40 freq:5200
[ 1303.899464] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1303.899464] FD Interval should be a factor of BI.
[ 1303.899464] Disabling FD
[ 1303.899464]
[ 1303.899716] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1303.899716] FD Interval should be a factor of BI.
[ 1303.899716] Disabling FD
[ 1303.899716]
[ 1303.899790] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1303.899840] wlan: [0:I:ANY] vdev[4]: Mgt Rate:6000(kbps)
[ 1303.903839] wlan: [12540:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath01 : clone params: 0x00000001
[ 1303.903908] wlan: [12540:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 16:0c:6b
:44:ff:b0
[ 1303.903986] wlan: [12540:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ea0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x1
[ 1303.903986]
[ 1303.905095] wlan: [12540:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1303.905162] wlan: [12540:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1303.905172] wlan: [12540:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1303.905205] wlan: [12540:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
```

```
[ 1303.905301] wlan: [12540:I:ANY] MBO Initialized
[ 1303.905316] wlan: [12540:I:ANY] OCE Initialized
[ 1303.905354] wlan: [12540:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 54 nss_id -1
[ 1303.905363] wlan: [12540:I:ANY] NSS radio_if 46
[ 1303.905485] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1303.905508] wlan: [12540:I:ANY] osif_nss_ol_vap_create: 1393: vap create b4224600
: if_num 54
[ 1303.905910] wlan: [12540:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1303.905918] wlan: [12540:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1303.909428] wlan: [12540:I:ANY] VAP device ath01 created osifp: (b4224600) os_if:
(b33a8000)
[ 1304.134227] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:0
[ 1304.134227] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1304.134258] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1304.134278] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1304.328311] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
2 Max_mac_rings 1
[ 1304.328378] wlan: [2765:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type
1 Max_mac_rings 1
[ 1304.435413] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1304.435413] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1304.435443] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1305.090005] device ath01 entered promiscuous mode
[ 1305.090308] br-guest: port 7(ath01) entered forwarding state
[ 1305.090367] br-guest: port 7(ath01) entered forwarding state
[ 1305.110539] wlan: [2893:I:ANY] DES SSID SET=pocket-reality_optout
[ 1305.110563] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
30
[ 1305.110967] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1305.111623] wlan: [0:I:CMN_MLME] vdev[5] ieee chan:40 freq:5200
[ 1305.111977] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1305.111977] FD Interval should be a factor of BI.
[ 1305.111977] Disabling FD
[ 1305.111977]
[ 1305.112154] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1305.112154] FD Interval should be a factor of BI.
[ 1305.112154] Disabling FD
[ 1305.112154]
[ 1305.112213] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1305.112255] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1305.135188] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1305.135188] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1305.135225] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1305.402471] wlan: [13058:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1305.402486] wlan: [13058:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1305.415193] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1305.415852] wlan: [0:I:CMN_MLME] vdev[5] ieee chan:40 freq:5200
[ 1305.416166] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1305.416166] FD Interval should be a factor of BI.
[ 1305.416166] Disabling FD
[ 1305.416166]
[ 1305.416406] wlan: [0:E:FILS discovery] wlan_fd_set_valid_fd_period: 607: Invalid
FD Interval : 0. Valid range is 20 - 100ms.
[ 1305.416406] FD Interval should be a factor of BI.
[ 1305.416406] Disabling FD
[ 1305.416406]
[ 1305.416477] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1305.416520] wlan: [0:I:ANY] vdev[5]: Mgt Rate:6000(kbps)
[ 1305.436500] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
```

```
[ 1305.436500]
[ 1305.436532] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1305.436532]
[ 1305.447481] wlan: [13085:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath02 : clone params: 0x00005001
[ 1305.447573] wlan: [13085:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 1a:0c:6b
:44:ff:b0
[ 1305.447677] wlan: [13085:I:ANY] wlan_vap_create: 1599: devhandle=0xb4ea0500, opmo
de=IEEE80211_M_HOSTAP, flags=0x5001
[ 1305.447677]
[ 1305.448054] wlan: [13085:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1305.448117] wlan: [13085:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
e:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1305.448126] wlan: [13085:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1305.448150] wlan: [13085:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1305.448244] wlan: [13085:I:ANY] MBO Initialized
[ 1305.448252] wlan: [13085:I:ANY] OCE Initialized
[ 1305.448295] wlan: [13085:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 55 nss_id -1
[ 1305.448305] wlan: [13085:I:ANY] NSS radio_if 46
[ 1305.448377] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1305.448419] wlan: [13085:I:ANY] osif_nss_ol_vap_create: 1393: vap create ada55640
: if_num 55
[ 1305.448817] wlan: [13085:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1305.448826] wlan: [13085:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1305.452196] wlan: [13085:I:ANY] VAP device ath02 created osifp: (ada55640) os_if:
(a9738000)
[ 1305.561848] br-lan: port 7(ath0) entered learning state
[ 1305.743639] wlan: [13226:I:ANY] DES SSID SET=SM_1
[ 1305.811099] wlan: [13261:I:ANY] ieee80211_ucfg_set_freq_internal: 553:
[ 1305.811099] Channel is configured already!!
[ 1306.136375] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1306.136375]
[ 1306.136402] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1306.136402]
[ 1306.436870] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1306.436870]
[ 1306.436911] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1306.436911]
[ 1306.889232] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1306.890009] wlan: [0:I:CMN_MLME] vdev[6] ieee chan:40 freq:5200
[ 1306.890191] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1306.890247] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1306.890336] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 M
ax_mac_rings 1
[ 1306.890375] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 M
ax_mac_rings 1
[ 1306.890403] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 2 M
ax_mac_rings 1
[ 1306.890421] wlan: [0:I:Monitor Filter] dp_mon_ht2_rx_ring_cfg: 119: srng type 1 M
ax_mac_rings 1
[ 1307.081689] br-guest: port 7(ath01) entered forwarding state
[ 1307.106981] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1307.107696] wlan: [0:I:CMN_MLME] vdev[6] ieee chan:40 freq:5200
[ 1307.107902] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1307.107963] wlan: [0:I:ANY] vdev[6]: Mgt Rate:6000(kbps)
[ 1307.136892] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1307.136892]
[ 1307.136920] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1307.136920]
[ 1307.437174] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1307.437174]
[ 1307.437203] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1307.437203]
[ 1307.561719] br-lan: topology change detected, propagating
[ 1307.561744] br-lan: port 7(ath0) entered forwarding state
[ 1308.137464] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
```

```
[ 1308.137464]
[ 1308.137493] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1308.137493]
[ 1308.350986] wlan: [14363:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 11
[ 1308.351291] wlan: [14363:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=106
[ 1308.351299] wlan: [14363:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=122
[ 1308.351976] wlan: [14363:I:ANY] wlan_scan_update_channel_list: 1154: num_chan: 11
[ 1308.352109] wlan: [14363:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=106
[ 1308.352117] wlan: [14363:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_init_precac_list: 262
1: ieee=122
[ 1308.352147] wlan: [14363:I:ANY] number of channels: 2G = 0 5G = 11, 6G = 0
[ 1308.352187] wlan: [2838:I:ANY] ol_acfg_handle_wifi_ioctl: 446: ol_acfg_handle_wif
i_ioctl: req->cmd=76 not valid for radio interface, it's for VAP
[ 1308.437847] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1308.437847]
[ 1308.437881] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1308.437881]
[ 1308.674404] wlan: [14442:I:ANY] wlan_cfg80211_set_hwaddr: 6591: wlan_cfg80211_set
_hwaddr :10:0c:6b:44:ff:b1 ret: 0
[ 1308.715971] wlan: [14459:I:ANY] ol_ath_set_config_param: 1664: set TXBF_SND_PERIO
D: value 100 wmi_status 0
[ 1308.856141] wlan: [0:I:ANY] dp_lag_soc_enable: 102: pdev(a7c6d444) Enabling DBDC
Repeater 0
[ 1308.856200] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1308.856209] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1308.856266] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1308.856274] wlan: [0:E:NSS] [nss-wifili]: NSS Wifili DBDC Repeater enable message
passed
[ 1308.945193] wlan: [0:I:ANY] ol_ath_set_config_param: 2416: Disconnect_timeout val
ue: 10
[ 1308.992919] wlan: [0:I:ANY] ol_ath_set_config_param: 2422: Reconfiguration_timeou
t value:60
[ 1309.142133] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1309.142133]
[ 1309.142158] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1309.142158]
[ 1309.392505] wlan: [14685:I:ANY] wlan_cfg80211_add_virtual_intf: 335: proprietary
mode 6 for interface: ath2 : clone params: 0x00000001
[ 1309.392569] wlan: [14685:I:ANY] osifp_create_wlan_vap: 9618: VDEV Create 10:0c:6b
:44:ff:b1
[ 1309.392650] wlan: [14685:I:ANY] wlan_vap_create: 1599: devhandle=0xb4f40500, opmo
de=IEEE80211_M_HOSTAP, flags=0x1
[ 1309.392650]
[ 1309.393000] wlan: [14685:I:ANY] ol_ath_vap_set_param: 1198: Setting SGI value: 1
[ 1309.393041] wlan: [14685:I:ANY] ol_ath_vap_set_param: 2230: VDEV params:HE su_bfe
:1|su_bfer:1|mu_bfee:0|mu_bfer:1|dl_muofdma:1|ul_muofdma:1|ul_mumimo:1|dl_muofdma_b
fer:0
[ 1309.393048] wlan: [14685:I:ANY] ol_ath_vap_set_param: 2243: he_bf_cap=0x7b
[ 1309.393067] wlan: [14685:I:ANY] ol_ath_vap_set_param: 2258: VDEV params:AC/VHT so
unding mode:HE|SU/MU sounding mode:SU|Trig/Non-Trig sounding mode:Non-Triggered
[ 1309.393141] wlan: [14685:I:ANY] MBO Initialized
[ 1309.393149] wlan: [14685:I:ANY] OCE Initialized
[ 1309.393179] wlan: [14685:I:ANY] osif_nss_ol_vap_create: 1281: NSS wifi offload VA
P create IF 56 nss_id -1
[ 1309.393188] wlan: [14685:I:ANY] NSS radio_if 48
[ 1309.393255] wlan: [0:I:ANY] osif_nss_vdev_cfg_callback: 1006: VDEV configuration
success: 0
[ 1309.393274] wlan: [14685:I:ANY] osif_nss_ol_vap_create: 1393: vap create b8cb0500
: if_num 56
[ 1309.393625] wlan: [14685:I:ANY] osif_create_vap_complete: 9826: TX Checksum:1|SG:
1|TSO:1|LRO:0
[ 1309.393632] wlan: [14685:I:ANY] WLAN-NSS: VAP NSS ops initialized
[ 1309.398064] wlan: [14685:I:ANY] VAP device ath2 created osifp: (b8cb0500) os_if:
(a97c0000)
[ 1309.418066] device ath2.4093 entered promiscuous mode
[ 1309.418083] device ath2 entered promiscuous mode
[ 1309.418969] br-guest: port 8(ath2.4093) entered forwarding state
```

```
[ 1309.419060] br-guest: port 8(ath2.4093) entered forwarding state
[ 1309.433671] device ath2.4094 entered promiscuous mode
[ 1309.434563] br-lan: port 8(ath2.4094) entered listening state
[ 1309.434637] br-lan: port 8(ath2.4094) entered listening state
[ 1309.438666] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1309.438666]
[ 1309.438697] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1309.438697]
[ 1310.142372] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1310.142372]
[ 1310.142398] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1310.142398]
[ 1310.439620] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1310.439620]
[ 1310.439671] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1310.439671]
[ 1310.850364] wlan: [2893:I:ANY] DES SSID SET=NETGEAR_ORBI_hidden43
[ 1310.850383] wlan: [2893:I:ANY] wlan_cfg80211_set_phymode: 1215: desired hw mode:
30
[ 1310.850963] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1310.866310] wlan: [0:I:CMN_MLME] vdev[7] ieee chan:108 freq:5540
[ 1310.866696] wlan: [0:I:ANY] vdev[7]: Mgt Rate:6000(kbps)
[ 1310.867033] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5500.
[ 1310.867033]
[ 1310.867065] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5520.
[ 1310.867065]
[ 1310.867086] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5540.
[ 1310.867086]
[ 1310.867113] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5560.
[ 1310.867113]
[ 1310.920585] wlan: [15249:I:ANY] wlan_cfg80211_set_wiphy_params: 1970: WARNING: Fr
agmentation with HT mode NOT ALLOWED!!
[ 1310.930118] wlan: [0:I:dfs] WLAN_DEBUG_DFS_ALWAYS : dfs_set_current_channel_for_f
req: 894: dfs_curchan already updated
[ 1310.944632] wlan: [0:I:CMN_MLME] vdev[7] ieee chan:108 freq:5540
[ 1310.944902] wlan: [0:I:ANY] vdev[7]: Mgt Rate:6000(kbps)
[ 1310.945311] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5500.
[ 1310.945311]
[ 1310.945350] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5520.
[ 1310.945350]
[ 1310.945373] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5540.
[ 1310.945373]
[ 1310.945396] wlan: [6102:I:ANY] ieee80211_dfs_deliver_event: dfs CAC_START event d
elivered on chan freq 5560.
[ 1310.945396]
[ 1311.142819] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1311.142819]
[ 1311.142848] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1311.142848]
[ 1311.411711] br-guest: port 8(ath2.4093) entered forwarding state
[ 1311.431709] br-lan: port 8(ath2.4094) entered learning state
[ 1311.832858] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1311.832858]
[ 1311.832887] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1311.832887]
[ 1312.143770] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1312.143770]
[ 1312.143797] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1312.143797]
[ 1312.833774] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1312.833774]
[ 1312.833824] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1312.833824]
[ 1313.144483] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1313.144483]
```



```
[ 1313.144518] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1313.144518]
[ 1313.431706] br-lan: topology change detected, propagating
[ 1313.431723] br-lan: port 8(ath2.4094) entered forwarding state
[ 1313.835200] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1313.835200]
[ 1313.835231] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1313.835231]
[ 1314.145373] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1314.145373]
[ 1314.145400] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1314.145400]
[ 1314.836478] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1314.836478]
[ 1314.836507] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1314.836507]
[ 1315.146344] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1315.146344]
[ 1315.146370] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1315.146370]
[ 1315.837404] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1315.837404]
[ 1315.837435] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1315.837435]
[ 1316.146574] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1316.146574]
[ 1316.146606] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1316.146606]
[ 1316.838319] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1316.838319]
[ 1316.838360] wlan: [2765:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1316.838360]
[ 1317.147531] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:293
[ 1317.147531]
[ 1317.147558] wlan: [2766:I:ANY] ald_nl_receive: Invalid interface index:301
[ 1317.147558]
[ 1317.488212] wlan: [17438:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1317.488226] wlan: [17438:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
[ 1317.488264] wlan: [17438:I:ANY] wlan_set_param: 952: Configure hifi 952 entry_cn
t 2
[ 1317.555521] wlan: [17447:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1317.555535] wlan: [17447:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
[ 1317.555573] wlan: [17447:I:ANY] wlan_set_param: 952: Configure hifi 952 entry_cn
t 2
[ 1317.651047] wlan: [17469:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1317.651061] wlan: [17469:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
[ 1317.718371] wlan: [17502:I:ANY] osif_nss_vdev_set_cfg: 2056: setting me mode 5 ta
rget type 0
[ 1317.718385] wlan: [17502:I:ANY] osif_nss_vdev_set_cfg: 2060: Mcast command 5
```