

```
!Current Configuration:
!
!System Description "M4200-10MG-PoE+ ProSAFE 8-port 2.5 Gigabit L2+
Intelligent Edge Managed Switch with 2 10G Uplinks, 12.0.2.36, 1.0.0.6"
!System Software Version "12.0.2.36"
!System Up Time "145 days 19 hrs 1 mins 29 secs"
!Additional Packages QOS,IPv6,IPv6 Management,Routing
!Current SNTP Synchronized Time: SNTP Last Attempt Status Is Not
Successful
!
vlan database
vlan 201,901
vlan routing 1 1
vlan routing 201 2
vlan routing 901 3
exit
configure
ip redirects
ip icmp error-interval 1000000 200
username "admin" password
928336800ccca32a4c218d5e93108e70239a6a11664300a29598ec3b4771b69fd1711bccc
d59d465b2309c18879c50347d786118e6d332a4b21b337c620dcc5c level 15
encrypted
username snmpv3 authentication "admin" md5
line console
exit
line telnet
exit
line ssh
exit
snmp-server sysname "BS Router"
!
interface 0/5
bandwidth 100000
description 'TO ER'
mtu 1550
switchport trunk allowed vlan 1-4092
routing
ip address 10.48.0.2 255.255.255.0
ip mtu 1500
no poe
exit
interface 0/6
bandwidth 1000000
description 'BS SWITCH'
mtu 1550
switchport mode trunk
switchport trunk allowed vlan 201,901
vlan ingressfilter
ip mtu 1550
no poe
exit
interface vlan 1
routing
```

```
ip address dhcp
exit
interface vlan 201
routing
ip address 192.168.200.254 255.255.255.0
exit
interface vlan 901
routing
ip address 192.168.210.254 255.255.255.0
exit
router rip
exit
ip default-gateway 10.48.0.1
ip route 10.80.0.0 255.255.255.0 192.168.210.2
exit
```