

Mail - Akshay.Marali... M4250-26G4F-PoE+ x NETGEAR - Common Account Management - Google Chrome

192.168.0.110:49151/v1

NETGEAR
M4250-26G4F-PoE+ 26x1G PoE+ 300W and 4xSFP

System Switching Routing QoS
Management Device View License Services IP

Management System Configuration

- Initial Setup
- System Information
- System CPU Status
- Switch Statistics
- USB Device Information
- Loopback Interface
- Management Interfaces
- Time
- DNS
- SDM Template Preference
- Green Ethernet
- Bonjour
- PTP TC

Admin Password
Enable Password
System Name
System Location
System Contact
SNTP Mode
SNTP Server
Designated Source Interfa
IPv4 Management VLAN C
Management VLAN ID
Routing Mode
IPv4 Address Assignment
IPv6 Management VLAN C

Create Account

orbi. NIGHTHAWK. NETGEAR INSIGHT. Meural

Email Address:

Confirm Email Address:

First Name:

Last Name:

Password:

Confirm Password:

Choose Country:

Yes! Please keep me updated via personalised marketing emails about products and services from NETGEAR Inc. and NETGEAR International Limited, great tips and tricks and feature enhancements. You can withdraw this consent with future effect by clicking the unsubscribe link at the bottom of each marketing email. Please see our [Privacy Policy](#) for more information.

By checking this box, clicking Next, I accept NETGEAR's Terms and Conditions and acknowledge that I have read the [Privacy Policy](#).

Welcome admin

Cancel Apply

Gateway 0.0.0.0

VLAN Reset

• Basic Reset Configuration

• Advanced

• VLAN Configuration

- VLAN Trunking Configuration
- VLAN Membership
- VLAN Status
- Port PVID Configuration
- MAC Based VLAN
- Protocol Based VLAN Group Configuration
- Protocol Based VLAN Group Membership
- IP Subnet Based VLAN
- Port DVLAN Configuration
- Voice VLAN Configuration
- GARP Switch Configuration

Internal VLAN Configuration

Internal VLAN Allocation Base:

Internal VLAN Allocation Policy: Ascending Descending

VLAN Configuration

<input type="checkbox"/>	VLAN ID	VLAN Name	VLAN Type	Make Static
<input type="checkbox"/>				Disable
<input type="checkbox"/>	1	default	Default	Disable
<input type="checkbox"/>	10	KPMG-test	Static	Disable
<input type="checkbox"/>	1675	QSC-AV	Static	Disable

- VLAN
- Basic
- Advanced
 - VLAN Configuration
 - VLAN Trunking Configuration
 - VLAN Membership**
 - VLAN Status
 - Port PVID Configuration
 - MAC Based VLAN
 - Protocol Based VLAN Group Configuration
 - Protocol Based VLAN Group Membership
 - IP Subnet Based VLAN
 - Port DVLAN Configuration
 - Voice VLAN Configuration
 - GARP Switch Configuration

VLAN Membership

VLAN ID:

Group Operation:

VLAN Name:

VLAN Type:

Ports

1	3	5	7	9	11	13	15	17	19	21	23	25	27	29
2	4	6	8	10	12	14	16	18	20	22	24	26	28	30

LAG

1	3	5	7	9	11	13	15	17	19	21	23
2	4	6	8	10	12	14	16	18	20	22	24



- VLAN
- Basic
- Advanced
 - VLAN Configuration
 - VLAN Trunking Configuration
 - VLAN Membership**
 - VLAN Status
 - Port PVID Configuration
 - MAC Based VLAN
 - Protocol Based VLAN Group Configuration
 - Protocol Based VLAN Group Membership
 - IP Subnet Based VLAN
 - Port DVLAN Configuration
 - Voice VLAN Configuration
 - GARP Switch Configuration

VLAN Membership

VLAN ID: 1675
Group Operation: Untag All
VLAN Name: CSC-AV
VLAN Type: Static

Ports

1	3	5	7	9	11	13	15	17	19	21	23	25	27	29
U	U	U	U	U	U	U	U	U	U	U	U	U	U	U
2	4	6	8	10	12	14	16	18	20	22	24	26	28	30
U	U	U	U	U	U	U	U	U	U	U	U	U	U	U

LAG

1	3	5	7	9	11	13	15	17	19	21	23
U	U	U	U	U	U	U	U	U	U	U	U
2	4	6	8	10	12	14	16	18	20	22	24
U	U	U	U	U	U	U	U	U	U	U	U

- VLAN
- Basic
- Advanced
 - VLAN Configuration
 - VLAN Trunking Configuration
 - VLAN Membership**
 - VLAN Status
 - Port PVID Configuration
 - MAC Based VLAN
 - Protocol Based VLAN Group Configuration
 - Protocol Based VLAN Group Membership
 - IP Subnet Based VLAN
 - Port DVLAN Configuration
 - Voice VLAN Configuration
 - GARP Switch Configuration

VLAN Membership

VLAN ID: 1675
Group Operation: Untag All
VLAN Name: CSC AV
VLAN Type: Static

Ports

1	3	5	7	9	11	13	15	17	19	21
U	U	U	U	U	U	U	U	U	U	U
2	4	6	8	10	12	14	16	18	20	22

LAG

1	3	5	7	9	11	13	15	17	19	21	23
U	U	U	U	U	U	U	U	U	U	U	U
2	4	6	8	10	12	14	16	18	20	22	24

Alert

Unable to set VLAN membership for VLAN (1675), Change the port to general mode, and then try again.

OK

NETGEAR

M4250-26G4F-PoE+ 26x1G PoE+ 300W and 4xSFP Managed Switch

Welcome admin

- System
- Switching
- Routing
- QoS
- Security
- Monitoring
- Maintenance
- Help
- Index

VLAN Auto-VoIP STP Multicast MVR Address Table Ports LAG L2 Loop Protection

Apply Cancel

VLAN Membership

VLAN ID: 10
Group Operation: Untag All
VLAN Name: X7MC-Test
VLAN Type: Static

Ports

1	3	5	7	9	11	13	15	17	19	21
2	4	6	8	10	12	14	16	18	20	22

LAG

1	3	5	7	9	11	13	15	17	19	21	23
2	4	6	8	10	12	14	16	18	20	22	24

Alert

Unable to set VLAN membership for VLAN (10)

OK

© 2020 NETGEAR, Inc. All rights reserved.



M4250-26G4F-PoE+ 26x1G PoE+ 300W and 4xSFP Managed Switch

Welcome admin

System Switching Routing QoS Security Monitoring Maintenance Help Index

VLAN Auto-VoIP STP Multicast MVR Address Table Ports LAG L2 Loop Protection

VLAN	Auto-VoIP	STP	Multicast	MVR	Address Table	Ports	LAG	L2 Loop Protection	Cancel	Apply		
<input type="checkbox"/> 0/1	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/2	1675	1675			None	Admit All	Enable	Enable	1,1675	None	None	None
<input type="checkbox"/> 0/3	1675	1675			None	Admit All	Enable	Enable	1,1675	None	None	None
<input type="checkbox"/> 0/4	1675	1675			None	Admit All	Enable	Enable	1,1675	None	None	None
<input type="checkbox"/> 0/5	1675	1675			None	Admit All	Enable	Enable	1,1675	None	None	None
<input type="checkbox"/> 0/6	1675	1675			None	Admit All	Enable	Enable	1,1675	None	None	None
<input type="checkbox"/> 0/7	1675	1675			None	Admit All	Enable	Enable	1,1675	None	None	None
<input type="checkbox"/> 0/8	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/9	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/10	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/11	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/12	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/13	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/14	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/15	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/16	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/17	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/18	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/19	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/20	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/21	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/22	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/23	1675	1675			None	Admit All	Enable	Enable	1	None	None	None
<input type="checkbox"/> 0/24	1675	1675			None	Admit All	Enable	Enable	1	None	None	None

© 2020 NETGEAR, Inc. All rights reserved.

- Basic
- Advanced
- VLAN Configuration
- VLAN Trunking Configuration
- VLAN Membership
- VLAN Status**
- Port PVID Configuration
- MAC Based VLAN
- Protocol Based VLAN Group Configuration
- Protocol Based VLAN Group Membership
- IP Subnet Based VLAN
- Port DVLAN Configuration
- Voice VLAN Configuration
- GARP Switch Configuration

VLAN Status

VLAN ID	VLAN Name	VLAN Type	Routing Interfaces	Member Ports
1	default	Default	4/1	
10	KPMG-test	Static		
1675	QSC-AV	Static	4/2	0/1 - 0/30, lag 1 - lag 24