

```
SYSTEM CONFIG FILE ::= BEGIN
! Model: GS728TPv2
! System Description: NETGEAR 24-Port Gigabit PoE+ Smart Managed Pro Switch with
4 SFP Ports (GS728TPv2)
! Firmware Version: 6.0.2.5 [Nov 28 2019 - 16:49:51]
! Loader Version: 1.0.0.5 [2017-12-28 09:35:22 UTC]
! Config Version: 0
! System Name: Rental Switch B
! MAC Address: 3C:37:86:CB:9C:02
! Serial Number: 5WA1997CA070C
! System Up Time: 0 days, 0 hours, 30 mins, 1 secs
!
!
!
system name "Rental Switch B"
system location "Rental Area"
system contact
ip address 192.168.0.239 mask 255.255.255.0
ip name-server
sccd
!
username "admin" secret encrypted MoQ+ApVBxpb6ZLgXW91+2w==
snmp 1 host time-b.netgear.com port 123 ver 4
snmp 2 host time-a.netgear.com port 123 ver 4
snmp 3 host 0.openwrt.pool.ntp.org port 123 ver 4
!
!
vlan 4088
  name "Auto-VoIP"
vlan 4089
  name "Auto-Video"
vlan 15,60
voice-vlan oui 0 0:1:e3 SIEMENS
voice-vlan oui 1 0:3:6b CISCO1
voice-vlan oui 2 0:12:43 CISCO2
voice-vlan oui 3 0:60:b9 NITSUKO
voice-vlan oui 4 0:d0:1e PINTEL
voice-vlan oui 5 0:e0:75 VERILINK
voice-vlan oui 6 0:e0:bb 3COM
voice-vlan oui 7 0:4:d AVAYA1
voice-vlan oui 8 0:1b:4f AVAYA2
!
!
!
!
!
!
power inline powerup-mode staggered
spanning-tree mst configuration
  name "3C-37-86-CB-9C-02"
!
!
!
!
```

```
!  
snmp user "admin" "AUTH" auth md5 encrypted MoQ+ApVBxpb6ZLgxW91+2w==  
!  
!  
!  
!  
!  
ip http session-softtimeout 60  
!  
!  
!  
!  
!  
!  
!  
!  
!  
interface vlan15  
  ip address 192.168.15.20/24  
interface vlan60  
  ip address 192.168.60.1/24  
interface g1  
!  
interface g2  
!  
interface g3  
  switchport hybrid pvid 15  
  switchport hybrid allowed vlan add 15 untagged  
  switchport hybrid allowed vlan remove 1  
!  
interface g4  
  switchport hybrid pvid 15  
  switchport hybrid allowed vlan add 15 untagged  
  switchport hybrid allowed vlan remove 1  
!  
interface g5  
  switchport hybrid pvid 15  
  switchport hybrid allowed vlan add 15 untagged  
  switchport hybrid allowed vlan remove 1  
!  
interface g6  
  switchport hybrid pvid 15  
  switchport hybrid allowed vlan add 15 untagged  
  switchport hybrid allowed vlan remove 1  
!  
interface g7  
!  
interface g8  
!  
interface g9  
!  
interface g10  
!
```

```
interface g11
!
interface g12
!
interface g13
!
interface g14
!
interface g15
!
interface g16
!
interface g17
!
interface g18
!
interface g19
!
interface g20
!
interface g21
  switchport hybrid pvid 60
  switchport hybrid allowed vlan add 60 untagged
  switchport hybrid allowed vlan remove 1
!
interface g22
  switchport hybrid pvid 60
  switchport hybrid allowed vlan add 60 untagged
  switchport hybrid allowed vlan remove 1
!
interface g23
  switchport hybrid pvid 60
  switchport hybrid allowed vlan add 60 untagged
  switchport hybrid allowed vlan remove 1
!
interface g24
  switchport hybrid pvid 60
  switchport hybrid allowed vlan add 60 untagged
  switchport hybrid allowed vlan remove 1
!
interface g25
!
interface g26
!
interface g27
!
interface g28
!
!
!
ip unicast-routing
ip route 0.0.0.0/0 192.168.15.1
ip route 192.168.15.0/24 192.168.15.1
ip route 192.168.60.0/24 192.168.15.1
```

