

```
10 ++++++X+++++
11 -----X+++++
12 ++++++X+++++
13 ----+X+++++
14 ++++++X+++++
15 ----+X+++++
```

NW0

```
00000000001111111122222222233333333334444444445555555556666
0123456789012345678901234567890123456789012345678901234567890123
```

```
00 -----X+++++
01 -----X+++++
02 -----X+++++
03 -----X+++++
04 -----X+++++
05 -----X+++++
06 -----X+++++
07 -----X+++++
08 -----X+++++
09 -----X+++++
10 -----X+++++
11 -----X+++++
12 -----X+++++
13 -----X+++++
14 -----X+++++
15 -----X+++++
```

WRDQW0

```
00000000001111111122222222233333333334444444445555555556666
0123456789012345678901234567890123456789012345678901234567890123
```

```
00 ++++++X+++++
01 ++++++X+++++
02 ++++++X+++++
03 ++++++X+++++
04 ++++++X+++++
05 ++++++X+++++
06 ++++++X+++++
07 ++++++X+++++
08 ++++++X+++++
09 ++++++X+++++
10 ++++++X+++++
11 ++++++X+++++
12 ++++++X+++++
13 ++++++X+++++
14 ++++++X+++++
15 ++++++X+++++
```

```
WRDMW0 00000031
WRDMW0 00000031
```

ADDR

00000000001111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 ++++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Committing NVRAM...done
Waiting for reset button release...done
Digital core power voltage set to 0.9375V
Decompressing...done
Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040273
00001D40

RDLYW0 00000004

RDENW0 00000041

RDQSW0

000000000011111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 -----+X+
01 -----+X+
02 -----+X+
03 -----+X+
04 -----+X+
05 -----+X+
06 -----+X+
07 -----+X+
08 -----+X+
09 -----+X+
10 -----+X+
11 -----+X+
12 -----+X+
13 -----+X+
14 -----+X+
15 -----+X+
```

PW0

000000000011111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 ++++X+++
01 ---+X+++
02 ++++X+++
03 -+++X+++
04 ++++X+++
05 ---+X+++
06 ++++X+++
07 ++++X+++
08 -+++X+++
09 ---+X+++
10 ---+X+++
11 ----X+++
12 ++++X+++
13 ---+X+++
14 ++++X+++
15 ----X+++
```

NW0

000000000011111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 -----+X+
01 -----+X+
02 -----+X+
03 -----+X+
04 -----+X+
05 -----+X+
06 -----+X+
07 -----+X+
```

```
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++
```

WRDQW0

```
000000000011111111122222222233333333334444444445555555556666
0123456789012345678901234567890123456789012345678901234567890123
```

```
00 ++++X+++++
01 ++++X+++++
02 ++++X+++++
03 ++++X+++++
04 ++++X+++++
05 ++++X+++++
06 ++++X+++++
07 ++++X+++++
08 ++++X+++++
09 -++++X+++++
10 ++++X+++++
11 -++++X+++++
12 ++++X+++++
13 ++++X+++++
14 ++++X+++++
15 ++++X+++++
```

WRDMW0 00000031
WRDMW0 00000031

ADDR

```
000000000011111111122222222233333333334444444445555555556666
0123456789012345678901234567890123456789012345678901234567890123
```

```
00 ++++S+X+++++
```

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31

Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena

Init Devs.

Boot up from NAND flash...

Bootcode Boot partition size = 524288(0x80000)

DDR Clock: 533 MHz

Info: DDR frequency set from clkfreq=800,*533*

et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Committing NVRAM...done
Waiting for reset button release...done
Digital core power voltage set to 0.9375V
Decompressing...done
Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC060118010800000000000001A103F01000000

S30040273
00001D10

RDLYW0 00000004

RDENW0 00000041

RDQSW0

00000000001111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 -----+++++X+++++
01 -----+++++X+++++
02 -----+++++X+++++
03 -----+++++X+++++
04 -----+++++X+++++
05 -----+++++X+++++
06 -----+++++X+++++
07 -----+++++X+++++
08 -----+++++X+++++
09 -----+++++X+++++
10 -----+++++X+++++
11 -----+++++X+++++
12 -----+++++X+++++
13 -----+++++X+++++
14 -----+++++X+++++

15 -----+++++X+++++

PW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -+++++X+++++
01 ---+++++X+++++
02 -+++++X+++++
03 -+++++X+++++
04 ++++++X+++++
05 ----+++++X+++++
06 ++++++X+++++
07 ++++++X+++++
08 --+++++X+++++
09 -----+++++X+++++
10 --+++++X+++++
11 -----+++++X+++++
12 -+++++X+++++
13 -----+++++X+++++
14 ++++++X+++++
15 -----+++++X+++++

NW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+++++X+++++
01 -----+++++X+++++
02 -----+++++X+++++
03 -----+++++X+++++
04 -----+++++X+++++
05 -----+++++X+++++
06 -----+++++X+++++
07 -----+++++X+++++
08 -----+++++X+++++
09 -----+++++X+++++
10 -----+++++X+++++
11 -----+++++X+++++
12 -----+++++X+++++
13 -----+++++X+++++
14 -----+++++X+++++
15 -----+++++X+++++

WRDQW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 ++++++X+++++
01 ++++++X+++++
02 ++++++X+++++
03 ++++++X+++++
04 ++++++X+++++
05 ++++++X+++++

```
06 +++++X+++++
07 +++++X+++++
08 +++++X+++++
09 -++++X+++++
10 +++++X+++++
11 -++++X+++++
12 +++++X+++++
13 +++++X+++++
14 +++++X+++++
15 +++++X+++++
```

WRDMW0 00000031
WRDMW0 00000031

ADDR

```
00000000001111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 +++++S+X+++++
```

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Committing NVRAM...done

Waiting for reset button release...doneDigital core power voltage set to 0.9375V

Decompressing...done

Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040277

00001D30

RDLYW0 00000004

RDENW0 00000040

RDQSW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

00 -----+++++++X+++++++
01 -----+++++++X+++++++
02 -----+++++++X+++++++
03 -----+++++++X+++++++
04 -----+++++++X+++++++
05 -----+++++++X+++++++
06 -----+++++++X+++++++
07 -----+++++++X+++++++
08 -----+++++++X+++++++
09 -----+++++++X+++++++
10 -----+++++++X+++++++
11 -----+++++++X+++++++
12 -----+++++++X+++++++
13 -----+++++++X+++++++
14 -----+++++++X+++++++
15 -----+++++++X+++++++

PW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

00 +++++X+++++
01 -++++X+++++
02 +++++X+++++
03 +++++X+++++
04 +++++X+++++
05 -++++X+++++
06 +++++X+++++
07 +++++X+++++
08 +++++X+++++
09 ---++++X+++++
10 +++++X+++++
11 ----++++X+++++

12 +++++X++++
13 --++++X++++
14 +++++X++++
15 ---++++X++++

NW0

0000000001111111112222222223333333334444444445555555556666
012345678901234567890123456789012345678901234567890123

00 -----X++++
01 -----X++++
02 -----X++++
03 -----X++++
04 -----X++++
05 -----X++++
06 -----X++++
07 -----X++++
08 -----X++++
09 -----X++++
10 -----X++++
11 -----X++++
12 -----X++++
13 -----X++++
14 -----X++++
15 -----X++++

WRDQW0

0000000001111111112222222223333333334444444445555555556666
012345678901234567890123456789012345678901234567890123

00 +++++X++++
01 +++++X++++
02 +++++X++++
03 +++++X++++
04 +++++X++++
05 +++++X++++
06 +++++X++++
07 +++++X++++
08 +++++X++++
09 -++++X++++
10 +++++X++++
11 -++++X++++
12 +++++X++++
13 +++++X++++
14 +++++X++++
15 +++++X++++

WRDMW0 00000031
WRDMW0 00000031

ADDR

0000000001111111112222222223333333334444444445555555556666

0123456789012345678901234567890123456789012345678901234567890123
00 ++++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Committing NVRAM...done
Waiting for reset button release...donDigital core power voltage set to 0.9375V
Decompressing...done
Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040277
00001D20

RDLYW0 00000004

RDENW0 00000041

RDQSW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++

PW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 ++++X+++++
01 ---+++X+++++
02 -++++X+++++
03 ++++X+++++
04 ++++X+++++
05 ---+++X+++++
06 ++++X+++++
07 ++++X+++++
08 ---+++X+++++
09 ----+++X+++++
10 ---+++X+++++
11 -----+X+++++
12 -++++X+++++
13 ----+++X+++++
14 ++++X+++++
15 ----+++X+++++

NW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++

```
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++
```

WRDQW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 ++++X+++++
01 ++++X+++++
02 ++++X+++++
03 ++++X+++++
04 ++++X+++++
05 ++++X+++++
06 ++++X+++++
07 ++++X+++++
08 ++++X+++++
09 -+++X+++++
10 ++++X+++++
11 -+++X+++++
12 ++++X+++++
13 ++++X+++++
14 ++++X+++++
15 ++++X+++++
```

WRDMW0 00000031

WRDMW0 00000031

ADDR

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 ++++S+X+++++
```

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31

Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena

Init Devs.

Boot up from NAND flash...

Bootcode Boot partition size = 524288(0x80000)

DDR Clock: 533 MHz

Info: DDR frequency set from clkfreq=800,*533*

et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31

Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena

Init Devs.

Boot up from NAND flash...

Bootcode Boot partition size = 524288(0x80000)

DDR Clock: 400 MHz

Info: DDR frequency set from clkfreq=800,*533*

Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.

et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Committing NVRAM...done

Waiting for reset button release...done
Digital core power voltage set to 0.9375V

Decompressing...done

Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040277

00001D50

RDLYW0 00000004

RDENW0 00000041

RDQSW0

00000000001111111112222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++

01 -----+X+++++

02 -----+X+++++

03 -----+X+++++

04 -----+X+++++

05 -----+X+++++

06 -----+X+++++

07 -----+X+++++

08 -----+X+++++

09 -----+X+++++

10 -----+X+++++

11 -----+X+++++

12 -----+X+++++

13 -----+X+++++

14 -----+X+++++

15 -----+X+++++

PW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -++++X+++++
01 ---++X+++++
02 -++++X+++++
03 +++++X+++++
04 +++++X+++++
05 ---++X+++++
06 +++++X+++++
07 +++++X+++++
08 -++++X+++++
09 -----X+++++
10 -++++X+++++
11 -----++X+++++
12 -++++X+++++
13 -----X+++++
14 +++++X+++++
15 -----++X+++++

NW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++

WRDQW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 +++++X+++++
01 +++++X+++++
02 +++++X+++++
03 +++++X+++++
04 +++++X+++++
05 +++++X+++++

06 +++++X+++++
07 +++++X+++++
08 +++++X+++++
09 -++++X+++++
10 +++++X+++++
11 -++++X+++++
12 +++++X+++++
13 +++++X+++++
14 +++++X+++++
15 +++++X+++++

WRDMW0 00000031
WRDMW0 00000031

ADDR

00000000001111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 +++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Committing NVRAM...done

Waiting for reset button release...doneDigital core power voltage set to 0.9375V

Decompressing...done

Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S3004026F

00001D40

RDLYW0 00000004

RDENW0 00000039

RDQSW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

```

00 -----+++++X+++++
01 -----+++++X+++++
02 -----+++++X+++++
03 -----+++++X+++++
04 -----+++++X+++++
05 -----+++++X+++++
06 -----+++++X+++++
07 -----+++++X+++++
08 -----+++++X+++++
09 -----+++++X+++++
10 -----+++++X+++++
11 -----+++++X+++++
12 -----+++++X+++++
13 -----+++++X+++++
14 -----+++++X+++++
15 -----+++++X+++++

```

PW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

```

00 +++++X+++++
01 -++++X+++++
02 +++++X+++++
03 +++++X+++++
04 +++++X+++++
05 -++++X+++++
06 +++++X+++++
07 +++++X+++++
08 +++++X+++++
09 ---++++X+++++
10 +++++X+++++
11 ---++++X+++++

```


12 ++++++X+++++
13 ---+++++X+++++
14 ++++++X+++++
15 ---+++++X+++++

NW0

00000000011111111122222222233333333334444444445555555556666
012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++

WRDQW0

00000000011111111122222222233333333334444444445555555556666
012345678901234567890123456789012345678901234567890123

00 ++++++X+++++
01 ++++++X+++++
02 ++++++X+++++
03 ++++++X+++++
04 ++++++X+++++
05 ++++++X+++++
06 ++++++X+++++
07 ++++++X+++++
08 ++++++X+++++
09 ++++++X+++++
10 ++++++X+++++
11 ++++++X+++++
12 ++++++X+++++
13 ++++++X+++++
14 ++++++X+++++
15 ++++++X+++++

WRDMW0 00000031
WRDMW0 00000031

ADDR

00000000011111111122222222233333333334444444445555555556666

0123456789012345678901234567890123456789012345678901234567890123
00 ++++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Committing NVRAM...done
Waiting for reset button release...donDigital core power voltage set to 0.9375V
Decompressing...done
Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040273
00001D50

RDLYW0 00000004

RDENW0 00000041

RDQSW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++

PW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 ++++X+++++
01 ---++X+++++
02 ++++X+++++
03 -+++X+++++
04 ++++X+++++
05 ---++X+++++
06 ++++X+++++
07 ++++X+++++
08 --++X+++++
09 ----X+++++
10 --++X+++++
11 ----X+++++
12 ++++X+++++
13 ----X+++++
14 ++++X+++++
15 ----X+++++

NW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++

```
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++
```

WRDQW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 ++++X+++++
01 ++++X+++++
02 ++++X+++++
03 ++++X+++++
04 ++++X+++++
05 ++++X+++++
06 ++++X+++++
07 ++++X+++++
08 ++++X+++++
09 -+++X+++++
10 ++++X+++++
11 -+++X+++++
12 ++++X+++++
13 ++++X+++++
14 ++++X+++++
15 ++++X+++++
```

WRDMW0 00000031

WRDMW0 00000031

ADDR

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 ++++S+X+++++
```

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31

Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena

Init Devs.

Boot up from NAND flash...

Bootcode Boot partition size = 524288(0x80000)

DDR Clock: 533 MHz

Info: DDR frequency set from clkfreq=800,*533*

et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Committing NVRAM...done
Waiting for reset button release...done
Digital core power voltage set to 0.9375V
Decompressing...done
Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040277
00001D40

RDLYW0 00000004

RDENW0 00000041

RDQSW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 -----+++++X+++++
01 -----+++++X+++++
02 -----+++++X+++++
03 -----+++++X+++++
04 -----+++++X+++++
05 -----+++++X+++++
06 -----+++++X+++++
07 -----+++++X+++++
08 -----+++++X+++++
09 -----+++++X+++++
10 -----+++++X+++++
11 -----+++++X+++++
12 -----+++++X+++++
13 -----+++++X+++++
14 -----+++++X+++++

15 -----+++++X+++++

PW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 +++++X+++++
01 ---++++X+++++
02 +++++X+++++
03 +++++X+++++
04 +++++X+++++
05 ---++++X+++++
06 +++++X+++++
07 +++++X+++++
08 -++++X+++++
09 -----X+++++
10 --++++X+++++
11 ----++++X+++++
12 +++++X+++++
13 ----++++X+++++
14 +++++X+++++
15 ----++++X+++++

NW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----X+++++
01 -----X+++++
02 -----X+++++
03 -----X+++++
04 -----X+++++
05 -----X+++++
06 -----X+++++
07 -----X+++++
08 -----X+++++
09 -----X+++++
10 -----X+++++
11 -----X+++++
12 -----X+++++
13 -----X+++++
14 -----X+++++
15 -----X+++++

WRDQW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 +++++X+++++
01 +++++X+++++
02 +++++X+++++
03 +++++X+++++
04 +++++X+++++
05 +++++X+++++

06 +++++X+++++
07 +++++X+++++
08 +++++X+++++
09 -++++X+++++
10 +++++X+++++
11 -++++X+++++
12 +++++X+++++
13 +++++X+++++
14 +++++X+++++
15 +++++X+++++

WRDMW0 00000031
WRDMW0 00000031

ADDR

00000000001111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 +++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Committing NVRAM...done

Waiting for reset button release...doneDigital core power voltage set to 0.9375V

Decompressing...done

Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S3004027F

00001D40

RDLYW0 00000004

RDENW0 00000041

RDQSW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

00 -----+++++++X+++++++
01 -----+++++++X+++++++
02 -----+++++++X+++++++
03 -----+++++++X+++++++
04 -----+++++++X+++++++
05 -----+++++++X+++++++
06 -----+++++++X+++++++
07 -----+++++++X+++++++
08 -----+++++++X+++++++
09 -----+++++++X+++++++
10 -----+++++++X+++++++
11 -----+++++++X+++++++
12 -----+++++++X+++++++
13 -----+++++++X+++++++
14 -----+++++++X+++++++
15 -----+++++++X+++++++

PW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

00 -+++++++X+++++++
01 ---+++++++X+++++++
02 -+++++++X+++++++
03 -+++++++X+++++++
04 ++++++++X+++++++
05 ----+++++++X+++++++
06 ++++++++X+++++++
07 ++++++++X+++++++
08 -+++++++X+++++++
09 -----+++++++X+++++++
10 --+++++++X+++++++
11 -----+++++++X+++++++


```
12 ++++++X+++++
13 ----+X+++++
14 ++++++X+++++
15 ----+X+++++
```

NW0

```
00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
```

```
00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++
```

WRDQW0

```
00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
```

```
00 ++++++X+++++
01 ++++++X+++++
02 ++++++X+++++
03 ++++++X+++++
04 ++++++X+++++
05 ++++++X+++++
06 ++++++X+++++
07 ++++++X+++++
08 ++++++X+++++
09 ++++++X+++++
10 ++++++X+++++
11 ++++++X+++++
12 ++++++X+++++
13 ++++++X+++++
14 ++++++X+++++
15 ++++++X+++++
```

```
WRDMW0 00000031
WRDMW0 00000031
```

ADDR

```
00000000001111111112222222223333333333444444444455555555556666
```

0123456789012345678901234567890123456789012345678901234567890123
00 ++++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Committing NVRAM...done
Waiting for reset button release...donDigital core power voltage set to 0.9375V
Decompressing...done
Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S3004026F
00001D30

RDLYW0 00000004

RDENW0 00000041

RDQSW0

000000000011111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++

PW0

000000000011111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -+X+++++
01 ---+X+++++
02 +++X+++++
03 -+X+++++
04 +++X+++++
05 ---+X+++++
06 +++X+++++
07 +++X+++++
08 --+X+++++
09 ----+X+++++
10 --+X+++++
11 ----+X+++++
12 +++X+++++
13 ---+X+++++
14 +++X+++++
15 ----+X+++++

NW0

000000000011111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++

```
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++
```

WRDQW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 ++++X+++++
01 ++++X+++++
02 ++++X+++++
03 ++++X+++++
04 ++++X+++++
05 ++++X+++++
06 ++++X+++++
07 ++++X+++++
08 ++++X+++++
09 -++++X+++++
10 ++++X+++++
11 -++++X+++++
12 ++++X+++++
13 ++++X+++++
14 ++++X+++++
15 ++++X+++++
```

WRDMW0 00000031
WRDMW0 00000031

ADDR

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

```
00 ++++S+X+++++
```

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena

Init Devs.

Boot up from NAND flash...

Bootcode Boot partition size = 524288(0x80000)

DDR Clock: 533 MHz

Info: DDR frequency set from clkfreq=800,*533*

et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31

Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena

Init Devs.

Boot up from NAND flash...

Bootcode Boot partition size = 524288(0x80000)

DDR Clock: 400 MHz

Info: DDR frequency set from clkfreq=800,*533*

Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.

et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Committing NVRAM...done

Waiting for reset button release...done
Digital core power voltage set to 0.9375V

Decompressing...done

Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S3004026F

00001CE0

RDLYW0 00000004

RDENW0 00000039

RDQSW0

00000000001111111112222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

00 -----+++++X+++++
01 -----+++++X+++++
02 -----+++++X+++++
03 -----+++++X+++++
04 -----+++++X+++++
05 -----+++++X+++++
06 -----+++++X+++++
07 -----+++++X+++++
08 -----+++++X+++++
09 -----+++++X+++++
10 -----+++++X+++++
11 -----+++++X+++++
12 -----+++++X+++++
13 -----+++++X+++++
14 -----+++++X+++++

15 -----+X+++++

PW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 ++++X+++++
01 -+++X+++++
02 ++++X+++++
03 ++++X+++++
04 ++++X+++++
05 ++++X+++++
06 ++++X+++++
07 ++++X+++++
08 ++++X+++++
09 ---+++X+++++
10 ++++X+++++
11 ---+++X+++++
12 ++++X+++++
13 ---+++X+++++
14 ++++X+++++
15 ---+++X+++++

NW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 -----+X+++++
01 -----+X+++++
02 -----+X+++++
03 -----+X+++++
04 -----+X+++++
05 -----+X+++++
06 -----+X+++++
07 -----+X+++++
08 -----+X+++++
09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++

WRDQW0

00000000001111111112222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 ++++X++++-
01 ++++X++++-
02 ++++X++++-
03 ++++X++++-
04 ++++X++++-
05 ++++X++++-

06 +++++X+++++
07 +++++X+++++
08 +++++X+++++
09 -++++X+++++
10 +++++X+++++
11 -++++X+++++
12 +++++X+++++
13 +++++X+++++
14 +++++X+++++
15 +++++X+++++

WRDMW0 00000031
WRDMW0 00000031

ADDR

00000000001111111122222222223333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 +++++S++X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Committing NVRAM...done

Waiting for reset button release...doneDigital core power voltage set to 0.9375V

Decompressing...done

Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040277

00001D20

RDLYW0 00000004

RDENW0 00000041

RDQSW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

```

00 -----+++++++X+++++++
01 -----+++++++X+++++++
02 -----+++++++X+++++++
03 -----+++++++X+++++++
04 -----+++++++X+++++++
05 -----+++++++X+++++++
06 -----+++++++X+++++++
07 -----+++++++X+++++++
08 -----+++++++X+++++++
09 -----+++++++X+++++++
10 -----+++++++X+++++++
11 -----+++++++X+++++++
12 -----+++++++X+++++++
13 -----+++++++X+++++++
14 -----+++++++X+++++++
15 -----+++++++X+++++++

```

PW0

000000000011111111122222222223333333333444444444455555555556666

0123456789012345678901234567890123456789012345678901234567890123

```

00 -+++++++X+++++++
01 ---+++++++X+++++++
02 -+++++++X+++++++
03 -+++++++X+++++++
04 ++++++++X+++++++
05 ----+++++++X+++++++
06 ++++++++X+++++++
07 ++++++++X+++++++
08 -+++++++X+++++++
09 -----+++++++X+++++++
10 ---+++++++X+++++++
11 -----+++++++X+++++++

```



```
12 ++++++X+++++
13 -----X+++++
14 ++++++X+++++
15 -----X+++++
```

NW0

```
00000000001111111112222222223333333333444444444455555555556666
012345678901234567890123456789012345678901234567890123
```

```
00 -----X+++++
01 -----X+++++
02 -----X+++++
03 -----X+++++
04 -----X+++++
05 -----X+++++
06 -----X+++++
07 -----X+++++
08 -----X+++++
09 -----X+++++
10 -----X+++++
11 -----X+++++
12 -----X+++++
13 -----X+++++
14 -----X+++++
15 -----X+++++
```

WRDQW0

```
00000000001111111112222222223333333333444444444455555555556666
012345678901234567890123456789012345678901234567890123
```

```
00 ++++++X+++++
01 ++++++X+++++
02 ++++++X+++++
03 ++++++X+++++
04 ++++++X+++++
05 ++++++X+++++
06 ++++++X+++++
07 ++++++X+++++
08 ++++++X+++++
09 ++++++X+++++
10 ++++++X+++++
11 ++++++X+++++
12 ++++++X+++++
13 ++++++X+++++
14 ++++++X+++++
15 ++++++X+++++
```

```
WRDMW0 00000031
WRDMW0 00000031
```

ADDR

```
00000000001111111112222222223333333333444444444455555555556666
```

0123456789012345678901234567890123456789012345678901234567890123
00 ++++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 533 MHz
Info: DDR frequency set from clkfreq=800,*533*
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set
load default!
Digital core power voltage set to 0.9375V
Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31
Build Date: Tue Apr 14 17:28:19 CST 2015
Init Arena
Init Devs.
Boot up from NAND flash...
Bootcode Boot partition size = 524288(0x80000)
DDR Clock: 400 MHz
Info: DDR frequency set from clkfreq=800,*533*
Warning: invalid DDR setting of 533 MHz ignored. DDR frequency will be set to 400 MHz.
et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)
CPU type 0x0: 800MHz
Tot mem: 262144 KBytes

Committing NVRAM...done
Waiting for reset button release...donDigital core power voltage set to 0.9375V
Decompressing...done
Digital core power voltage set to 0.9375V

SHMOO VER 1.13

PKID07DC06011801080000000000001A103F01000000

S30040273
00001D10

RDLYW0 00000004

RDENW0 00000041

RDQSW0

```
0000000000111111111222222222333333333344444444445555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 -----+X+
01 -----+X+
02 -----+X+
03 -----+X+
04 -----+X+
05 -----+X+
06 -----+X+
07 -----+X+
08 -----+X+
09 -----+X+
10 -----+X+
11 -----+X+
12 -----+X+
13 -----+X+
14 -----+X+
15 -----+X+
```

PW0

```
0000000000111111111222222222333333333344444444445555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 ++++X++++
01 ---+++X+++
02 ++++X++++
03 -+++X+++
04 ++++X++++
05 ---+++X+++
06 ++++X++++
07 -+++X+++
08 ---+++X+++
09 ----+++X+++
10 -+++X+++
11 ----+++X+++
12 -+++X+++
13 ---+++X+++
14 ++++X++++
15 ----+++X+++
```

NW0

```
0000000000111111111222222222333333333344444444445555555556666
0123456789012345678901234567890123456789012345678901234567890123
00 -----+X+
01 -----+X+
02 -----+X+
03 -----+X+
04 -----+X+
05 -----+X+
06 -----+X+
07 -----+X+
08 -----+X+
```

09 -----+X+++++
10 -----+X+++++
11 -----+X+++++
12 -----+X+++++
13 -----+X+++++
14 -----+X+++++
15 -----+X+++++

WRDQW0

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 ++++X+++++
01 ++++X+++++
02 ++++X+++++
03 ++++X+++++
04 ++++X+++++
05 ++++X+++++
06 ++++X+++++
07 ++++X+++++
08 ++++X+++++
09 -++++X+++++
10 ++++X+++++
11 -++++X+++++
12 ++++X+++++
13 ++++X+++++
14 ++++X+++++
15 ++++X+++++

WRDMW0 00000031
WRDMW0 00000031

ADDR

0000000000111111111222222222233333333333444444444455555555556666
0123456789012345678901234567890123456789012345678901234567890123

00 ++++S+X+++++

Decompressing...done

CFE for Foxconn Router R6400 version: v1.0.31

Build Date: Tue Apr 14 17:28:19 CST 2015

Init Arena

Init Devs.

Boot up from NAND flash...

Bootcode Boot partition size = 524288(0x80000)

DDR Clock: 533 MHz

Info: DDR frequency set from clkfreq=800,*533*

et0: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

et1: Broadcom BCM47XX 10/100/1000 Mbps Ethernet Controller 6.37.15.1 (r407936)

CPU type 0x0: 800MHz

Tot mem: 262144 KBytes

Device eth0: hwaddr 50-6A-03-BC-2B-B4, ipaddr 192.168.1.1, mask 255.255.255.0
gateway not set, nameserver not set

1