```
LeafNets  Link encap:Ethernet  HWaddr 4a:c9:b1:31:59:b9
          inet addr:5.192.92.26  Bcast:5.255.255.255  Mask:255.0.0.0
          inet6 addr: fe80::48c9:b1ff:fe31:59b9/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST  MTU:1400  Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
          TX packets:663 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:0 (0.0 B)  TX bytes:254078 (248.1 KiB)

eth0      Link encap:Ethernet  HWaddr a0:63:91:ba:f2:2a
          UP BROADCAST MULTICAST  MTU:1500  Metric:1
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0
          TX packets:0 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:0 (0.0 B)  TX bytes:0 (0.0 B)

eth1      Link encap:Ethernet  HWaddr a0:63:91:ba:f2:2b
          inet addr:192.168.1.37  Bcast:192.168.1.255  Mask:255.255.255.0
          inet6 addr: fe80::a263:91ff:feba:f22b/64 Scope:Link
          UP BROADCAST RUNNING MULTICAST DYNAMIC  MTU:1500  Metric:1
          RX packets:1427175 errors:72922 dropped:21246 overruns:0
frame:78055
          TX packets:1316499 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1000
          RX bytes:1728758838 (1.6 GiB)  TX bytes:464847016 (443.3 MiB)

lo        Link encap:Local Loopback
          inet addr:127.0.0.1  Mask:255.0.0.0
          inet6 addr: ::1/128 Scope:Host
          UP LOOPBACK RUNNING  MTU:65536  Metric:1
          RX packets:486 errors:0 dropped:0 overruns:0 frame:0
          TX packets:486 errors:0 dropped:0 overruns:0 carrier:0
          collisions:0 txqueuelen:1
          RX bytes:44635 (43.5 KiB)  TX bytes:44635 (43.5 KiB)

Kernel IP routing table
Destination     Gateway         Genmask         Flags   MSS Window  irtt
Iface
0.0.0.0         192.168.1.1     0.0.0.0         UG        0 0          0
eth1
192.168.1.0     0.0.0.0         255.255.255.0   U         0 0          0
eth1
192.168.1.1     0.0.0.0         255.255.255.255 UH        0 0          0
eth1
Settings for eth0:
      Supported ports: [ TP MII ]
      Supported link modes:   10baseT/Half 10baseT/Full
                              100baseT/Half 100baseT/Full
                              1000baseT/Full
      Supported pause frame use: No
      Supports auto-negotiation: Yes
      Advertised link modes:  10baseT/Half 10baseT/Full
                              100baseT/Half 100baseT/Full
                              1000baseT/Full
      Advertised pause frame use: No
      Advertised auto-negotiation: Yes
      Speed: 10Mb/s
      Duplex: Half
```

```
      Port: MII
      PHYAD: 4
      Transceiver: external
      Auto-negotiation: on
      Supports Wake-on: pg
      Wake-on: g
      Current message level: 0x00000007 (7)
                         drv probe link
      Link detected: no
Settings for eth1:
      Supported ports: [ TP MII ]
      Supported link modes:   10baseT/Half 10baseT/Full
                              100baseT/Half 100baseT/Full
                              1000baseT/Full
      Supported pause frame use: No
      Supports auto-negotiation: Yes
      Advertised link modes:  10baseT/Half 10baseT/Full
                              100baseT/Half 100baseT/Full
                              1000baseT/Full
      Advertised pause frame use: No
      Advertised auto-negotiation: Yes
      Link partner advertised link modes:  10baseT/Half 10baseT/Full
                                           100baseT/Half 100baseT/Full
                                           1000baseT/Half 1000baseT/Full
      Link partner advertised pause frame use: Symmetric Receive-only
      Link partner advertised auto-negotiation: Yes
      Speed: 1000Mb/s
      Duplex: Full
      Port: MII
      PHYAD: 5
      Transceiver: external
      Auto-negotiation: on
      Supports Wake-on: pg
      Wake-on: g
      Current message level: 0x00000007 (7)
                         drv probe link
      Link detected: yes
/net/connman/service/ethernet_a06391baf22b_cable
  Type = ethernet
  Security = [  ]
  State = ready
  Favorite = True
  Immutable = False
  AutoConnect = True
  Name = Wired
  Ethernet = [ Method=auto, Interface=eth1, Address=A0:63:91:BA:F2:2B,
MTU=1500 ]
  IPv4 = [ Method=dhcp, Address=192.168.1.37, Netmask=255.255.255.0,
Gateway=192.168.1.1 ]
  IPv4.Configuration = [ Method=dhcp ]
  IPv6 = [  ]
  IPv6.Configuration = [ Method=auto, Privacy=disabled ]
  Nameservers = [ 192.168.1.1 ]
  Nameservers.Configuration = [  ]
  Timeservers = [ 192.168.1.1, time-e.netgear.com, time-a.netgear.com ]
  Timeservers.Configuration = [  ]
  Routes = [  ]
  Routes.Configuration = [  ]
```

```
Domains = [  ]
Domains.Configuration = [  ]
Proxy = [ Method=direct ]
Proxy.Configuration = [  ]
Provider = [  ]
```