

eth0 Link encap:Ethernet HWaddr b0:b9:8a:43:a2:b0  
inet addr:192.168.2.231 Bcast:192.168.2.255 Mask:255.255.255.0  
inet6 addr: fe80::b2b9:8aff:fe43:a2b0/64 Scope:Link  
UP BROADCAST RUNNING MULTICAST DYNAMIC MTU:9000 Metric:1  
RX packets:54098124 errors:0 dropped:211 overruns:0 frame:0  
TX packets:146940314 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:1000  
RX bytes:26109950762 (24.3 GiB) TX bytes:198277176605 (184.6 GiB)  
Memory:dfef0000-dfef7fff

eth1 Link encap:Ethernet HWaddr b0:b9:8a:43:a2:b1  
inet addr:192.168.2.223 Bcast:192.168.2.255 Mask:255.255.255.0  
inet6 addr: fe80::b2b9:8aff:fe43:a2b1/64 Scope:Link  
UP BROADCAST RUNNING MULTICAST DYNAMIC MTU:1500 Metric:1  
RX packets:395509 errors:0 dropped:142 overruns:0 frame:0  
TX packets:4439 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:1000  
RX bytes:96000749 (91.5 MiB) TX bytes:1311349 (1.2 MiB)  
Memory:dfef4000-dfef5fff

eth2 Link encap:Ethernet HWaddr b0:b9:8a:43:a2:b2  
UP BROADCAST MULTICAST MTU:1500 Metric:1  
RX packets:0 errors:0 dropped:0 overruns:0 frame:0  
TX packets:0 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:1000  
RX bytes:0 (0.0 B) TX bytes:0 (0.0 B)  
Memory:dfef2000-dfef3fff

eth3 Link encap:Ethernet HWaddr b0:b9:8a:43:a2:b3  
UP BROADCAST MULTICAST MTU:1500 Metric:1  
RX packets:0 errors:0 dropped:0 overruns:0 frame:0  
TX packets:0 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:1000  
RX bytes:0 (0.0 B) TX bytes:0 (0.0 B)  
Memory:dfef0000-dfef1fff

lo Link encap:Local Loopback  
inet addr:127.0.0.1 Mask:255.0.0.0  
inet6 addr: ::1/128 Scope:Host  
UP LOOPBACK RUNNING MTU:65536 Metric:1  
RX packets:4248081 errors:0 dropped:0 overruns:0 frame:0  
TX packets:4248081 errors:0 dropped:0 overruns:0 carrier:0  
collisions:0 txqueuelen:1  
RX bytes:493831978 (470.9 MiB) TX bytes:493831978 (470.9 MiB)

Kernel IP routing table

Destination	Gateway	Genmask	Flags	MSS	Window	irtt	Iface
0.0.0.0	192.168.2.1	0.0.0.0	UG	0 0	0		eth0
192.168.2.0	0.0.0.0	255.255.255.0	U	0 0	0		eth0
192.168.2.0	0.0.0.0	255.255.255.0	U	0 0	0		eth1
192.168.2.1	0.0.0.0	255.255.255.255	UH	0 0	0		eth1
192.168.2.1	0.0.0.0	255.255.255.255	UH	0 0	0		eth0

iface eth0 inet dhcp

mtu 9000

Settings for eth0:

Supported ports: [ TP ]

Supported link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Supported pause frame use: Symmetric

Supports auto-negotiation: Yes

Advertised link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Advertised pause frame use: Symmetric

Advertised auto-negotiation: Yes

Speed: 1000Mb/s

Duplex: Full

Port: Twisted Pair

PHYAD: 0

Transceiver: internal

Auto-negotiation: on

MDI-X: on (auto)

Supports Wake-on: pumbg

Wake-on: d

Current message level: 0x00000007 (7)

drv probe link

Link detected: yes

Settings for eth1:

Supported ports: [ TP ]

Supported link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Supported pause frame use: Symmetric

Supports auto-negotiation: Yes

Advertised link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Advertised pause frame use: Symmetric  
Advertised auto-negotiation: Yes  
Speed: 1000Mb/s  
Duplex: Full  
Port: Twisted Pair  
PHYAD: 1  
Transceiver: internal  
Auto-negotiation: on  
MDI-X: off (auto)  
Supports Wake-on: pumbg  
Wake-on: d  
Current message level: 0x00000007 (7)  
drv probe link

Link detected: yes

Settings for eth2:

Supported ports: [ TP ]  
Supported link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Supported pause frame use: Symmetric  
Supports auto-negotiation: Yes  
Advertised link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Advertised pause frame use: Symmetric  
Advertised auto-negotiation: Yes  
Speed: Unknown!  
Duplex: Unknown! (255)  
Port: Twisted Pair  
PHYAD: 2  
Transceiver: internal  
Auto-negotiation: on  
MDI-X: off (auto)  
Supports Wake-on: pumbg  
Wake-on: d  
Current message level: 0x00000007 (7)  
drv probe link

Link detected: no

Settings for eth3:

Supported ports: [ TP ]  
Supported link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Supported pause frame use: Symmetric

Supports auto-negotiation: Yes  
Advertised link modes: 10baseT/Half 10baseT/Full  
100baseT/Half 100baseT/Full  
1000baseT/Full

Advertised pause frame use: Symmetric

Advertised auto-negotiation: Yes

Speed: Unknown!

Duplex: Unknown! (255)

Port: Twisted Pair

PHYAD: 3

Transceiver: internal

Auto-negotiation: on

MDI-X: off (auto)

Supports Wake-on: pumbg

Wake-on: d

Current message level: 0x00000007 (7)

drv probe link

Link detected: no

/net/connman/service/ethernet\_b0b98a43a2b0\_cable

Type = ethernet

Security = [ ]

State = ready

Favorite = True

Immutable = False

AutoConnect = True

Name = Wired

Ethernet = [ Method=auto, Interface=eth0, Address=B0:B9:8A:43:A2:B0, MTU=9000 ]

IPv4 = [ Method=manual, Address=192.168.2.231, Netmask=255.255.255.0,

Gateway=192.168.2.1 ]

IPv4.Configuration = [ Method=manual, Address=192.168.2.231, Netmask=255.255.255.0,

Gateway=192.168.2.1 ]

IPv6 = [ ]

IPv6.Configuration = [ Method=auto, Privacy=disabled ]

Nameservers = [ 192.168.2.1 ]

Nameservers.Configuration = [ 192.168.2.1 ]

Timeservers = [ 192.168.2.1, time-e.netgear.com, time-a.netgear.com ]

Timeservers.Configuration = [ ]

Routes = [ ]

Routes.Configuration = [ ]

Domains = [ ]

Domains.Configuration = [ ]

Proxy = [ Method=direct ]

Proxy.Configuration = [ ]

Provider = [ ]

/net/connman/service/ethernet\_b0b98a43a2b1\_cable

Type = ethernet

Security = [ ]

State = ready

Favorite = True

Immutable = True

AutoConnect = True

Name = Wired

Ethernet = [ Method=auto, Interface=eth1, Address=B0:B9:8A:43:A2:B1, MTU=1500 ]

IPv4 = [ Method=fixed, Address=192.168.2.223, Netmask=255.255.255.0,

Gateway=192.168.2.1 ]

IPv4.Configuration = [ Method=fixed, Address=192.168.2.223, Netmask=255.255.255.0,

Gateway=192.168.2.1 ]

IPv6 = [ ]

IPv6.Configuration = [ Method=auto, Privacy=disabled ]

Nameservers = [ 192.168.2.1 ]

Nameservers.Configuration = [ ]

Timeservers = [ 192.168.2.1, time-e.netgear.com, time-a.netgear.com ]

Timeservers.Configuration = [ ]

Routes = [ ]

Routes.Configuration = [ ]

Domains = [ ]

Domains.Configuration = [ ]

Proxy = [ Method=direct ]

Proxy.Configuration = [ ]

Provider = [ ]