



C7000-100NAS

Logout

Firmware Version
V1.01.34

BASIC


ADVANCED

- Home
- Cable Connection**
- Wireless
- Attached Devices
- Parental Controls
- ReadySHARE
- Guest Network

Cable Connection

6	Locked	QAM256	1	393000000 Hz	2.1 dBmV	41.4 dB	23	0
7	Locked	QAM256	2	399000000 Hz	2.1 dBmV	41.2 dB	12	0
8	Locked	QAM256	3	405000000 Hz	2.2 dBmV	41.4 dB	10	0
9	Locked	QAM256	4	411000000 Hz	2.5 dBmV	41.6 dB	10	0
10	Locked	QAM256	5	417000000 Hz	2.8 dBmV	41.6 dB	6	0
11	Locked	QAM256	6	423000000 Hz	3 dBmV	42 dB	5	0
12	Locked	QAM256	7	429000000 Hz	3.2 dBmV	42 dB	5	0
13	Locked	QAM256	8	435000000 Hz	3.4 dBmV	42 dB	5	0
14	Locked	QAM256	9	453000000 Hz	3.7 dBmV	42.4 dB	2	0
15	Locked	QAM256	10	459000000 Hz	3.6 dBmV	42.3 dB	3	0
16	Locked	QAM256	11	465000000 Hz	3.4 dBmV	42.1 dB	7	0
17	Locked	QAM256	12	471000000 Hz	3.1 dBmV	42.5 dB	0	0
18	Locked	QAM256	14	483000000 Hz	3 dBmV	38.8 dB	0	0
19	Locked	QAM256	15	489000000 Hz	3.2 dBmV	39.4 dB	0	0
20	Locked	QAM256	16	495000000 Hz	3.3 dBmV	42.7 dB	0	0
21	Locked	QAM256	17	507000000 Hz	4 dBmV	40 dB	0	0
22	Locked	QAM256	18	513000000 Hz	4.1 dBmV	41.9 dB	0	0
23	Locked	QAM256	19	519000000 Hz	4.1 dBmV	43.1 dB	0	0
24	Locked	QAM256	20	525000000 Hz	4.2 dBmV	41.5 dB	0	0

Upstream Bonded Channels



Help Center

Show/Hide Help Center